



REPUBLIC OF THE PHILIPPINES  
**DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS**  
REGIONAL OFFICE III  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE  
SAN FRANCISCO ST., BRGY. PAMPANG, ANGELES CITY

QRF FY 2025 PROJECT  
DETAILED ENGINEERING DESIGN PLAN FOR THE  
REPAIR / REHABILITATION OF FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

NET LENGTH : 269.00 m. / 1,505.06 sq.m. Slope Protection

SUBMITTED:

**LOURDINO C. SORIANO**

CHIEF, PLANNING & DESIGN SECTION

DATE:

RECOMMENDED:

**AGUSTIN R. DAGSAAN JR.**

OIC, ASSISTANT DISTRICT ENGINEER

DATE:

APPROVED :

**ARNOLD R. OCAMPO**

DISTRICT ENGINEER

DATE:


QRF FY 2025 PROJECT  
DETAILED ENGINEERING DESIGN PLAN FOR THE

REPAIR / REHABILITATION OF FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

PROJECT SITE



VICINITY MAP  
SCALE NTS



SITE

LOCATION MAP  
SCALE NTS

| INDEX OF SHEETS |  |                                 |
|-----------------|--|---------------------------------|
| SHEET           |  | COVER PAGE                      |
| SHEET           |  | LOCATION MAP                    |
|                 |  | VICINITY MAP                    |
|                 |  | INDEX OF DRAWINGS               |
| SHEET           |  | GENERAL NOTES AND SYMBOLS       |
| SHEET           |  | TYPICAL DETAIL SLOPE PROTECTION |
| SHEET           |  | SUMMARY OF QUANTITIES           |
| SHEET           |  | PROFILE ELEVATION               |
| SHEET           |  | DIGITAL TERRAIN MODEL           |
| SHEET           |  | CROSS SECTIONS                  |
| SHEET           |  | DETAIL OF GROUND SILL           |
| SHEET           |  | DETAIL OF BILLBOARDS            |
| SHEET           |  | BORELOGS                        |



REPUBLIC OF THE PHILIPPINES  
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS  
REGIONAL OFFICE NO. III  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE  
ANGELES CITY

PROJECT NAME AND LOCATION :  
REPAIR / REHABILITATION OF  
FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT  
DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

SHEET CONTENTS :  
TITLE PAGE  
INDEX OF SHEETS  
LOCATION MAP  
VICINITY MAP

DRAFTED:  
**ERWIN S. DAVID**  
ENGINEERING ASSISTANT  
PREPARED:  
**GIE YANE S. MIRANDA**  
ENGINEER II

REVIEWED:  
**GIL A. RIVERA**  
ENGINEER II  
DATE

SUBMITTED:  
**LOURDINO C. SORIANO**  
CHIEF, PLANNING & DESIGN SECTION  
DATE

RECOMMENDED:  
**AGUSTIN N. DASSAAN JR.**  
OIC, ASSISTANT DISTRICT ENGINEER  
DATE

APPROVED:  
**ARNOLD N. OCAMPO**  
DISTRICT ENGINEER  
DATE

SHEET NO. SHEET NO.



## GENERAL NOTES :

## I. DESIGN CRITERIA

## A. Design Codes and Standards

1. DPWH Design Guidelines, Criteria and Standards, 2015 Edition
2. National Structural Code of the Philippines (NSCP), Volume I - Buildings, Towers and Other Vertical Structures, 5<sup>th</sup> Edition, 2001
3. National Structural Code of the Philippines (NSCP), Volume II - Bridges 2<sup>nd</sup> Edition, 1997
4. National Building Code of the Philippines (NBCP)
5. Philippine National Standards (PNS)
6. AASHTO Standard Specifications for Highway Bridges, 16<sup>th</sup> Edition, 1996
7. Standard Drawings for concrete Bridges (DPWH)
8. Technical Standards and Guidelines for Planning and Design (FCSEC), 2002

## II. SURVEY

## A. Specifications

1. DENR Administrative Order No. 2007-29

## B. Horizontal and Vertical Control

1. Basic traverse station were established based on station of existing KM post and permanent structures at the project site.
2. Elevation were assumed at the first benchmark at the beginning of each section of the project.
3. Benchmark were established at existing undisturbed structures at different intervals along the project.

## GENERAL NOTES

|                             |   |
|-----------------------------|---|
| Reference Benchmark Details |   |
| ELEVATION:                  |   |
| NORTHING:                   |   |
| EASTING:                    |   |
| Date of Survey              | PR 92, ZONE 3   |
| Equipment Used              | Leica Viva GNSS/GS15 Smart Antenna 555 channels (1)<br>Leica Captivate Controller/GS20 Data Field Controller (3)<br>Leica Viva GNSS/GS15 Smart Antenna 555 channels (3) |

## III. CONSTRUCTION

## A. Specifications

1. DPWH Design Guidelines, Criteria, and Standards (DGCS) - Volume III, 2015 Edition
2. The Item No. and description are taken from DPWH D.O. No. 5, series of 2017
3. DPWH Standard Specifications for Highways, Bridges and Airports - Vol. II, 2013 Edition
4. DPWH Standard Specifications for Public Works Structures (Buildings, Ports and Harbors, Flood Control and Drainage Structures and Water Supply Systems) - Vol. III, 2019 Edition

## B. Dimensions, Elevations and Stations

1. All dimensions are in millimeters unless otherwise specified.
2. All stations are in km + meter and elevations are in meters.
3. Figures shall govern over scaled dimension.
4. Reference datum Plane shall be the mean sea level. See General Plan, for benchmark locations.
5. All elevations are subject to change pending their verification during the Pre-construction Survey, based on the latest certified benchmarks of the NAMRIA.

## C. Civil Works

## 1. Structure Excavation

- a. Depth of excavation shall be as specified in the drawings.
- b. Post excavation surface shall be compacted to the required degree as specified in the plans.

## 2. Fill

- a. Filling materials shall be placed in layers of 250 mm max. thickness compacted and properly watered to attain at least 95 % of max. dry density.
- b. Truck dumping of materials in huge lumps shall not be permitted. The dump truck shall unload embankment materials by spreading it on top of the fill area sufficient to allow compaction by layers as specified.

## 3. Compaction

- a. Embankment materials shall be free from stones, twigs and other deleterious materials to ensure compaction and cohesion. Lumps of filling materials should be pulverized prior to compaction.
- b. Field Density Tests (FDT) for each compaction layer shall be undertaken until the required degree of compaction is attained, and under the supervision of the Materials Engineer.

## 4. Roadway

- a. Alignment and grades are subject to adjustment to suit existing field conditions.
- b. Clearing and grubbing shall be confined only within the limits of the acquired R.O.W.
- c. Unsuitable subgrade material shall be excavated to the required width and depth and replaced with approved material as directed by the Engineer. No embankment material shall be placed until foundation is suitable.
- d. Painting of metal beam guardrails pavement markings shall be considered subsidiary work only. No direct payment shall be made for this work except for specific items mentioned in the Bid Schedule.

## 5. Material Requirement

## a. Embankment Fill (Lahar)

1. Fill materials shall be obtained from borrow areas designated by the Consultant Materials Engineer.
2. At the designated source, the top 300 mm shall be scarified and should not be part of the filling material.

## b. Reinforced Concrete


## 1. Concrete

- a. Unless otherwise indicated, the compressive strength shall be  $f_c=35\text{MPa}$  for Pre-cast Panel, 24MPa for PCCP, RCBC and Side drainage structures @ 28 days, with max. water cement ratio of 0.53, slump range of 50-100 mm and max. size of aggregates shall be 40 mm.

## 2. Reinforcement


- a. Bars shall be of intermediate grade  $f_y=275\text{MPa}$ .
- b. Standard hooks shall be complied with at the free end of bar equivalent to 90° bend plus 12 db and minimum diameter for bends shall be 6db.
- c. Splicing of bars shall be by lapping or butt welding at 20 bar  $\phi$  or a minimum of 30 cm.
- d. Adjacent bars shall be securely held together by #16 tie-wires, each having a minimum length of 25 cm.
- e. Clear concrete cover between reinforcement bars and embankment materials shall be 75 mm and precast mortar blocks should be provide for this purpose.

## f. Cranked Splices



## Hooks and Bends

## DIMENSIONS OF 90-DEGREE AND 180-DEGREE HOOKS



| DIAMETER (mm) | 90° HOOK | 180° HOOK |
|---------------|----------|-----------|
| 10            | 160      | 105       |
| 12            | 195      | 115       |
| 16            | 260      | 150       |
| 20            | 320      | 180       |
| 25            | 400      | 200       |
| 28            | 480      | 255       |
| 32            | 545      | 290       |
| 36            | 615      | 325       |


## 3. Mixing Water

- a. Water to be used shall be clean and free from injurious amounts of oil, acid, alkali, salt, organic material and substances that may be deleterious to concrete or reinforcement.
- b. Non-potable water shall not be used unless it passes equivalent strength of at least 90% of the strength results of similar samples made using potable water with same proportions through compressive strength tests (ASTM C109).

## 4. Gabion Mattress

1. Mesh Properties  
Wire Diameter = 2.70 mm  
Selvage Wire Diameter = 3.40mm  
Tensile Strength (Minimum) = 4,700 kg./cm<sup>2</sup> (460 MPa)  
Compression Resistance = 300 - 400 tons/m<sup>2</sup>  
Filled Gabion Density = 17 kn/cum (min)  
Minimum Zinc Coating = 244.00 gm/m (ASTM A 641-82)  
Mesh Size = 6x6  
Tying / Connecting Wire = 2.70mm  
Wire Should Be Triple Twisted
2. Product tests shall be conducted on the product sample prior to its acceptance. Stones should be of durable pieces and resistant to weathering having a minimum density of 1.7 g/cc. at saturated surface dry (SSD) condition with sizes ranging from 100-200 mm in diameter, properly hand-laid for minimum voids.

## DIMENSIONS FOR STIRRUPS AND CROSSTIE HOOKS



| DIAMETER (mm) | 90° HOOK | 135° HOOK |
|---------------|----------|-----------|
| 10            | 120      | 125       |
| 12            | 125      | 130       |
| 16            | 160      | 200       |
| 20            | 320      | 250       |
| 25            | 400      | 315       |
| 28            | 480      | 365       |
| 32            | 545      | 420       |
| 36            | 615      | 470       |

## c. Geotextile Filter - 100% Polypropylene, non-woven geotextile, resistant to biological &amp; chemical environments.

- |                               |                                   |
|-------------------------------|-----------------------------------|
| Permeability                  | = 100 - 180 l/m <sup>2</sup> /sec |
| Pore Size                     | = 80 - 100 microns                |
| Tensile Strength CBR Puncture | = 10 KN/m (min)                   |
| Strength Grab Tensile         | = 2.1 KN (min)                    |
| Strength                      | = 500 N (min)                     |
| Thickness                     | = 1.2 mm (min)                    |
| Min. Overlap                  | = 0.30 m (min)                    |
| Bonding Medium                | = Mechanical (sewn)               |
- End weights shall be 12mm  $\phi$  RSB wrapped around at both edges of the geotextile, parallel to the bank, and held together by sewing.

## d. Sodding

1. The approved species of sod shall include roots and earth of at least 50 mm. thick.
2. Prior to placing of sod, the top soil should be sufficiently watered. The newly planted sod should be regularly watered by the contractor until plant growth is fully established and until their demobilization.
3. Coconut with Hydro seeding

## D. Others

Signboard showing name of project, station limits, package no. and name of contractor shall always be visible during construction until after the project has been accepted by the implementing agency. As-built drawings shall be done by the contractor based from the post construction survey of completed segments featuring deviations from the approved construction plans. The contractor shall prepare as built drawings on completed segment, as construction progresses to minimize the review period after construction. Subject for checking by the consultants.

## DESIGN PARAMETERS

## HYDRAULIC DESIGN DATA:

|  |   |
|--|---|
| CATCHMENT AREA                                 | = |
| RIVER LENGTH                                   | = |
| HIGHEST ELEVATION                              | = |
| LOWEST ELEVATION                               | = |
| DIFFERENCE IN ELEVATION                        | = |
| SLOPE  | = |
| Lca  | = |
| Ct   | = |
| MEAN VELOCITY                                  | = |
| LAG TIME                                       | = |
| ORDINARY WATER LEVEL                           | = |
| MAXIMUM EXPERIENCE FLOOD ELEV.                 | = |
| PEAK DISCHARGE (50 yrs. return period)         | = |
| DESIGN FLOOD ELEVATION (50 yrs. return period) | = |

## SYMBOLS AND ABBREVIATIONS

|  |                         |  |  |
|--|-------------------------|--|--|
|  | CONTOUR                 |  | EMBANKMENT & SLOPE PROTECTION  |
|  | DIKE                    |  | ORIENTATION  |
|  | RIVER / CREEK           |  | SECTION VIEW OF SLOPE PROTECTION   |
|  | CLAY/MOUNTAIN SOIL      |  | BENCH MARK   |
|  | EARTH SECTION           |  | BORE HOLE  |
|  | LIMIT                   |  | TEST PIT   |
|  | LIVIT OF DIMENSION      |  | IDENTIFICATION OF SECTION/DETAIL SHEET ON WHICH SECTION/DETAIL IS SHOWN IF DRAWING IS ON ANOTHER SHEET |
|  | INDICATION OF ELEVATION |  | DESIGN GRADE LINE  |
|  | EXISTING GRADE LINE     |  |  |

|  |                                      |
|--|--------------------------------------|
| PCCP - PORTLAND CEMENT CONCRETE PAVEMENT       | BM - BENCH MARK                      |
| AZIM - AZIMUTH                                 | e - RATE OF SUPER ELEVATION IN %     |
| DIST - DISTANCE                                | PC - POINT OF CURVATURE              |
| N - NORTHING                                   | PT - POINT OF TANGENCY               |
| E - EASTING                                    | AC - ASPHALT CONCRETE                |
| PI - POINT OF HORIZONTAL INTERSECTION          | cm - CENTIMETER                      |
| R - RADIUS                                     | mm - MILLIMETER                      |
| ΔR - OFFSET OF THE CIRCULAR CURVE              | Km - KILOMETER                       |
| T - TOTAL TANGENT LENGTH OF THE CIRCULAR CURVE | NC - NORMAL CROWN                    |
| Lc - LENGTH OF CIRCULAR CURVE                  | RCPC - REINFORCED CONC. PIPE CULVERT |
| D - DEGREE OF CURVE                            | DIA(Ø) - DIAMETER                    |
| E - TOTAL EXTERNAL DISTANCE                    | VAR - VARIES                         |
| PVI - POINT OF VERTICAL INTERSECTION           | INV ELEV(IE) - INVERT ELEVATION      |
| LVC - LENGTH OF VERTICAL CURVE                 | WEP - WOODEN ELECTRICAL POST         |
| Mo - MIDDLE ORDINATE                           | RCBC - REINF. CONCRETE BOX CULVERT   |
| g - GRADE IN PERCENT                           | ER - EDGE OF ROAD                    |
| ROW - RIGHT OF WAY                             | EL OR ELEV - ELEVATION               |



REPUBLIC OF THE PHILIPPINES  
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS  
REGIONAL OFFICE NO. III  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE  
ANGELAS CITY

PROJECT NAME AND LOCATION :

REPAIR / REHABILITATION OF  
FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT  
DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

SHEET CONTENTS :

GENERAL NOTES AND SYMBOLS

DRAWN BY :

ERWIN S. DAVID  
ENGINEERING ASSISTANT

PREPARED BY :

GIE YANE S. MIRANDA  
ENGINEER II

REVIEWED BY :

GIL A. RIVERA  
ENGINEER II

DATE :

SUBMITTED BY :

LOURDINO C. SORIANO  
CHIEF, PLANNING & DESIGN SECTION

DATE :

RECOMMENDED BY :

AGUSTIN R. DAGSAAN JR.  
DISTRICT ENGINEER

DATE :

APPROVED BY :

ARNOLD R. OCAMPO  
DISTRICT ENGINEER

DATE :

SET NO. :


1

SHEET NO. :



1



f = NOMINAL  
h = HEIGHT  
t<sub>w</sub> = WEB THICKNESS  
t<sub>f</sub> = FLANGE THICKNESS  
w = NOMINAL WIDTH




1. CLASS "A" CONCRETE SHALL BE USED WITH A MINIMUM COMPRESSIVE STRENGTH OF 20.70 MPa.
2. ALL REINFORCING BARS SHALL HAVE THE MINIMUM GRADE OF 40 ( $f_y = 276 \text{ MPa}$ ).
3. ALLOWABLE STRESS FOR STEEL SHEET PILE SHALL BE  $1800 \text{ kg/cm}^2$
4. THE CENTER OF LIFTING HOLE SHALL BE LOCATED AT DISTANCE OF 150mm FROM END OF EACH PILE. DIAMETER OF LIFTING HOLES SHALL BE 32mm.
5. ONE MAN BOULDERS (300-400mm DIA.) SHALL BE USED FOR THE BOULDER NEAR THE TOE OF THE FILL. ALL VOIDS BETWEEN BOULDERS SHALL BE FILLED WITH SAND AND GRAVEL AND SUFFICIENTLY WATERED TO SECURE COMPACTION.
6. DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
7. FIGURES SHALL GOVERN OVER SCALED DIMENSIONS IN CASE OF DISCREPANCIES.




DETAIL A


SCALE NTS




END PROTECTION  
SCALE 1 : 50



DETAIL OF STAIRS  
SCALE 1 : 50



DETAIL OF SLOPE PROTECTION  
SCALE 1 : 100

|  |   |   |   |  |   |   |   |         |           |
|--|---|---|---|--|---|---|---|---------|-----------|
|  <p>REPUBLIC OF THE PHILIPPINES<br/>DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS<br/>REGIONAL OFFICE NO. III<br/>PAMPANGA 3RD DISTRICT ENGINEERING OFFICE<br/>ANGELES CITY</p> | PROJECT NAME AND LOCATION :   | SHEET CONTENTS :                          | DRAWN BY:                                       | REVIEWED:                                      | SUBMITTED:  | RECOMMENDED:  | APPROVED:   | SET NO. | SHEET NO. |
|  | <p>REPAIR / REHABILITATION OF FLOOD CONTROL STRUCTURES ALONG ALASAS CREEK (LEFT DIKE), BRGY. SAN AGUSTIN, MAGALANG, PAMPANGA.</p> | <p>TYPICAL DETAIL OF SLOPE PROTECTION</p> | <p>ERWIN S. DAVID<br/>ENGINEERING ASSISTANT</p> | <p>GIL A. RIVERA<br/>ENGINEER II<br/>DATE:</p> | <p>LOURDINO C. SORIANO<br/>CHIEF, PLANNING &amp; DESIGN SECTION<br/>DATE:</p> | <p>AGUSTIN R. DAGSAYAN JR.<br/>OIC, ASSISTANT DISTRICT ENGINEER<br/>DATE:</p> | <p>ARNOLD R. OCAMPO<br/>DISTRICT ENGINEER<br/>DATE:</p> |         |           |

## SUMMARY OF QUANTITIES

| ITEM NO.  | DESCRIPTION                                      | QUANTITY | UNIT  | REMARKS |
|-----------|--|----------|-------|---------|
| B.4(10)   | Miscellaneous Survey and Staking                 | 1.00     | l.s.  |         |
| B.5       | Project Billboard / Signboard                    | 1.00     | ea.   |         |
| B.7(2)    | Occupational Safety and Health Program           | 1.00     | l.s.  |         |
| B.9       | Mobilization / Demobilization                    | 1.00     | l.s.  |         |
|           | TOTAL OF PART B                                  |          |       |         |
| PART C    | EARTHWORKS                                       |          |       |         |
| 101(1)    | Removal of Structures and Obstruction            | 1.00     | l.s.  |         |
|           | TOTAL OF PART C                                  |          |       |         |
| PART F    | BRIDGE CONSTRUCTION                              |          |       |         |
| 404(1)a   | Reinforcing Steel (Grade 40)                     | 7,070.78 | kg    |         |
| 405(1)a3  | Structural Concrete (20.68 Mpa Class A, 28 days) | 98.28    | cu.m. |         |
|           | TOTAL OF PART F                                  |          |       |         |
| PART L    | FLOOD AND RIVER CONTROL AND DRAINAGE             |          |       |         |
| 1700(1)   | Clearing and Grubbing                            | 4,020.35 | sq.m. |         |
| 1701(1)   | Unsuitable Excavation                            | 901.25   | cu.m. |         |
| 1704(1)b  | Embankment From Borrow (Common Soil)             | 2,585.65 | cu.m. |         |
| 1712(2)   | Concrete Slope Protection                        | 338.94   | cu.m. |         |
| 1717(2)a1 | Steel Sheet Pile (Slope Protection)              | 2,158.44 | m.    |         |



REPUBLIC OF THE PHILIPPINES  
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS  
REGIONAL OFFICE NO. III  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE  
ANGELES CITY

PROJECT NAME AND LOCATION :

REPAIR / REHABILITATION OF  
FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT  
DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

SHEET CONTENTS

SUMMARY OF QUANTITIES

DRAFTED

**ERWIN S. DAVID**  
ENGINEERING ASSISTANT

PREPARED

**GIE YANE S. MIRANDA**  
ENGINEER II

REVIEWED

**GIL A. RIVERA**  
ENGINEER II  
DATE

SUBMITTED

**LOURDINO C. SORIANO**  
CHIEF, PLANNING & DESIGN SECTION  
DATE

RECOMMENDED

**AGUSTIN R. DAGSAAN JR.**  
OIC, ASSISTANT DISTRICT ENGINEER  
DATE

APPROVED

**ARNOLD R. OCAMPO**  
DISTRICT ENGINEER  
DATE

SET NO.


SHEET NO.



# GUIDELINES ON THE INSTALLATION OF PROJECT BILLBOARDS:

- 1.) THE BILLBOARD DESIGN LAYOUT, DIMENSION AND LETTER SIZES ON WHITE BACKGROUND, AS SHOWN ON THE ATTACHED DRAWING, SHALL BE DEPICTED ON A STANDARD BILLBOARD MEASURING 1220mm X 2440mm (4ft. x 8ft.) USING 12.50mm (½ inch) THICK MARINE PLYWOOD OR TARPULIN OF THE SAME SIZE POSTED ON 5mm (¼ inch) MARINE PLYWOOD.
- 2.) ALL EXISTING BILLBOARD OF ON-GOING PROJECTS SHALL BE REPLACED WITH THE NEW ONE ADOPTING THE ABOVE GUIDELINES.
- 3.) FOR EACH BUILDING PROJECT, THE BILLBOARD SHALL BE INSTALLED IN FRONT OF THE PROJECT SITE.
- 4.) FOR EACH ROAD/BIDGE/FLOOD CONTROL PROJECT, TWO BILLBOARDS SHALL BE INSTALLED, ONE AT BEGINNING AND ONE AT THE END OF THE PROJECT.

- 5.) FOR ROAD PROJECTS WITH LENGTH OF 10 KILOMETERS OR MORE, ADDITIONAL BILLBOARD SHALL ALSO BE INSTALLED AT EVERY 5 KILOMETER INTERVAL.
- 6.) NAME(S) AND/OR PICTURE(S) OF ANY PERSONAGES SHOULD NOT APPEAR IN THE BILLBOARD.
- 7.) NO OTHER BILLBOARDS SHALL BE ALLOWED TO BE INSTALLED 100 METERS BEFORE AND 100 METERS AFTER ALL DPWH PROJECTS AND IN-BETWEEN THE PROJECT LIMITS OR WITHIN THE ROAD RIGHT-OF-WAY.
- 8.) DPWH CONTRACTORS SHALL NOT BE ALLOWED TO PLACE NAMES OF POLITICIANS OR CARRY POLITICAL BILLBOARD ON THEIR EQUIPMENT.



2440mm

THIS IS WHERE YOUR TAXES GO

NAME OF PROJECT: \_\_\_\_\_

LOCATION: \_\_\_\_\_

NAME OF CONTRACTOR: \_\_\_\_\_

DATE STARTED: \_\_\_\_\_

CONTRACT COMPLETION DATE: \_\_\_\_\_

CONTRACT COST: \_\_\_\_\_

IMPLEMENTING OFFICE: \_\_\_\_\_

SOURCES OF FUND: \_\_\_\_\_


Department of Public Works and Highways  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE

## DPWH STANDARD PROJECT BILLBOARD

## Notes:

1. For infrastructure projects, a tarpaulin signboard must be suitably framed for outdoor display at the project location, and shall be posted as soon as the award has been made.
2. The display and/or affixture of the picture, image, motto, logo, color, motif, initials or other symbol or graphic representation associated with the top leadership of the project proponent or implementing agency/office, on signboards, is considered unnecessary.

Specifications:  
Tarpaulin, White, 8ft x 8ft  
Resolution: 70dpi  
Font: Helvetica  
Font Size: Main Information - 3"  
Sub- Information - 1"  
Font Color: Black



## COMMISSION ON AUDIT REGIONAL OFFICE NO. III MAIMPIS, CITY OF SAN FERNANDO, PAMPANGA

PROJECT: \_\_\_\_\_ COST: \_\_\_\_\_

LOCATION: \_\_\_\_\_ FUND SOURCE(S): \_\_\_\_\_

Implementing Agency/ies: DPWH PAMPANGA 2ND D.E.O.

Development Partner/s: \_\_\_\_\_

Contractor / Supplier: \_\_\_\_\_

Brief Description of Project: \_\_\_\_\_

### Project Details:

| Project Date: |         |                           |                          | Project Status: |                       |                |         |
|---------------|---------|---------------------------|--------------------------|-----------------|-----------------------|----------------|---------|
| Duration      | Started | Target Date of Completion | Percentage of Completion | As of (Date)    | Cost Incurred to Date | Date Completed | Remarks |
|               |         |                           |                          |                 |                       |                |         |
|               |         |                           |                          |                 |                       |                |         |
|               |         |                           |                          |                 |                       |                |         |

For particulars or complaints about this project, please contact the Regional Office or Cluster which has audit jurisdiction on this project.

COA Regional Office No. /Cluster: III  
Address: Gov't Center, Maimpis, City of San Fernando, Pampanga  
Contact No: 4554296 or 4554272 or Text: COA Citizen's Desk at 0915-5391957.

## COA BILLBOARD



REPUBLIC OF THE PHILIPPINES  
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS  
REGIONAL OFFICE NO. III  
PAMPANGA 3RD DISTRICT ENGINEERING OFFICE  
ANGELUS CITY

PROJECT NAME AND LOCATION:

REPAIR / REHABILITATION OF  
FLOOD CONTROL STRUCTURES  
ALONG ALASAS CREEK (LEFT  
DIKE), BRGY. SAN AGUSTIN,  
MAGALANG, PAMPANGA.

SHEET CONTENTS:

DETAIL OF BILLBOARDS  
(COA AND DPWH)

DRAFTED

ERWIN S. DAVID  
ENGINEERING ASSISTANT

PREPARED

GIE YANE S. MIRANDA  
ENGINEER I

REVIEWED

GIL A. RIVERA  
ENGINEER II

SUBMITTED

LOURDINO C. SORIANO  
CHIEF, PLANNING & DESIGN SECTION

RECOMMENDED

AGUSTIN R. DAGSAM JR.  
DIO, ASSISTANT DISTRICT ENGINEER

APPROVED

ARNOLD R. OCAMPO  
DISTRICT ENGINEER

SET NO.

SHEET NO.