

REPUBLIC OF THE PHILIPPINES

DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS

MISAMIS ORIENTAL 2ND DISTRICT ENGINEERING OFFICE BALASE ST. EL SALVADOR CITY, MISAMIS ORIENTAL REGION - X

CONSTRUCTION OF RAINWATER COLLECTION SY DETAILED ENGINEERING DESIGN PLAN FOR C.Y. 2025 PROJECT

- INITAO CENTRAL SCHOOL, BRGY. POBLACION, INITAO, MISAMIS ORIENTAL
- INITAO NATIONAL COMPREHENSIVE HIGH SCHOOL, BRGY. POBLACION, INITAO, MISAMIS ORIENTAL
- INITAO COLLEGE, BRGY. JAMPASON, INITAO, MISAMIS ORIENTAL
- LIBERTAD NATIONAL HIGH SCHOOL, BRGY. POBLACION, LIBERTAD, MISAMIS ORIENTAL TESDA BUILDING, BRGY. POBLACION, LIBERTAD, MISAMIS ORIENTAL
- GSO BUILDING, BRGY. POBLACION, LIBERTAD, MISAMIS ORIENTAL


MARHNA A. RABANES
CHIEF, PLANNING AND DESIGN SECTION
DATE: anders.


RECOMMENDED

JIM B. RAMOS
ASSISTANT DISTRICT ENGINEER
DATE:


APPROVED:

ACHILLES B. PIMENTEL
DISTRICT ENGINEER
DATE:






PROPOSED LOCATION/MAP PLAN




MISAMIS ORIENTAL 2ND DISTRICT ENGINEERING OFFICE OF THE DISTRICT ENGINEER Balase St., El Salvador City, Misamis Oriental

REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
REGION - X







PERSPECTIVE & ISOMETRIC LAYOUT

PERSPECTIVE PLAN & ISOMETRIC LAYOUT

MISAMIS ORIENTAL 2ND DISTRICT ENGINEERING OFFICE OF THE DISTRICT ENGINEER Balese St., El Salvador City, Misarris Oriental

REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
REGION - X

PROJECT NAME AND LOCATION:

SHEET CONTENTS:

CY. 2025 PROJECT
DETAILED ENGINEERING DESIGN PLAN FOR
CONSTRUCTION OF RAINWATER
COLLECTOR SYSTEM,
LIBERTAD & INITAO, MISAMIS ORIENTAL

PREPARED:

NOLI LEMON M. NUEVAS ENGINEER II DATE

SUBMITTED:

MARINA A. RABANES
CHIEF, PLANNING AND DESIGN SECTION
DATE:

JIM B. RAMOS
ASSISTANT DISTRICT ENGINEER
DATE.

SET NO.

GENERAL NOTES FOR STRUCTURAL WORKS:

ALL WORKS AND MATERIALS SHALL COMPLY WITH THE TECHNICAL SPECIFICATIONS OF THIS PROJECT. ANY WORK OR MATERIAL NOT SPECIFICATIONS SHALL COMPLY WITH THE FOLLOWING NOTES AND BUILDING CODE REQUIREMENTS FOR CONCRETE AND REINFORCEMENT DETAILING.

a) ACI-318R-99 INSTITUTE

5 NSCP 2001-4TH EDITION NATIONAL STRUCTURAL CODE OF THE PHILIPPINES

MATERIALS

- 1. CONCRETE
- 9 UNLESS OTHERWISE INDICATED OR SPECIFIED ON THE PLANS, THE CONCRETE STRENGTH SHALL BE 20.7 MPg (3000psi)
- UNLESS OTHERWISE SHOWN ON THE DRAWINGS OR APPROVED, THE NOMINAL MAXIMUM SIZE AGGREGATE USED IN CONCRETE SHALL BE AS FOLLOWS:

5

- b.1) 37mm FOR CONCRETE IN WALLS, SLABS AND SECTIONS MORE THAN 600mm IN THICKNESS.
- b.2) 20mm FOR CONCRETE IN WALLS, SLABS AND SECTIONS BETWEEN 250mm AND 600mm IN
- THICKNESS.

 THICKNESS.

 12.5mm FOR THIN SECTION PRECAST CONCRETE AND SECOND STAGE CONCRETE FOR PLANT EMBEDMENT.

 2. REINFORCING STEEL
- 9
- 5 REINFORCING STEEL BARS SHALL BE DEFORMED CONFORMING TO ASTM A615M.
 UNLESS OTHERWISE INDICATED ON THE PLANS, THE REINFORCING STEEL GRADE SHALL BE: ·16MMØ AND LARGER GRADE 60 (Fy=415MPa)
- •12MM# AND SMALLER GRADE 40 (Fy=275MPa)
- ಲ REINFORCING STEEL SHALL BE FREE OF MILL SCALES, OR ANY SUBSTANCES WHICH WILL WEAKEN THE BOND WITH CONCRETE.
- SOIL BEARING CAPACITY
- ٥ ACTUAL SOIL BORING TEST, WHEN REQUIRED BY THE OWNER SHALL BE CONDUCTED PRIOR TO IMPLEMENTATION OF THE
- 5 PROJECT.

 PROJECT.

 THE CONTRACTOR SHALL INFORM THE STRUCTURAL ENGINEER REGARDING THE ACTUAL SOIL CONDITION DURING THE EXCAVATION OF FOOTING. FOOTING. Qa = 2,500psf (ASSUMED)

CONSTRUCTION

- 1. DIMENSIONS AND ELEVATIONS
- 0 ALL DIMENSIONS SHOWN IN THE DRAWINGS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- 5 ALL ELEVATIONS SHOWN IN THE DRAWINGS ARE IN METERS, AND ARE LOCALLY ESTABLISHED BASED ON TEMPORARY BENCH MARK OF THIS PROJECT.

 DEWATERING SHALL BE DONE PRIOR TO INSTALLATION OF REINFORCEMENT AND POURING OF CONCRETE FOR FOOTING.
- ೦
- 2. REINFORCED CONCRETE:

A) CONCRETE MIX AND PLACING

- 9 DESIGN OF CONCRETE MIX SHALL MEET THE MINIMUM DESIGN CONCRETE STRENGTH REQUIREMENTS AS SPECIFIED IN THE TECHNICAL SPECIFICATION AND AS GIVEN UNDER ITEM 1 OF MATERIALS.

 CONCRETE SHALL BE DEPOSITED, VIBRATED AND CURED IN ACCORDANCE WITH THE SPECIFICATIONS.
- 5

- c) UNLESS OTHERWISE SHOWN ON THE DRAWINGS, CONCRETE DEPOSITED AGAINST THE GROUND SHALL BE PROVIDED WITH LEVELLING CONCRETE WITH A MINIMUM THICKNESS OF 50mm PRIOR TO THE INSTALLATION OF STEEL REINFORCEMENT. THIS LEVELLING CONCRETE SHALL NOT BE CONSIDERED IN MEASURING THE STRUCTURAL DEPTH OF CONCRETE SECTION.

 d) THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER THE PLACING SEQUENCES OF STEEL REINFORCEMENT FOR ALL CONCRETING
- B) BAR BENDING, SPLICING AND PLACING

REINFORCING STEEL BARS SHALL NOT BE FIELD BENT UNLESS PERMITTED BY THE ENGINEER. INDICATING THE BENDING, CUTTING, SPLICING AND INSTALLATION OF ALL REINFORCING BARS.

- <u>_</u> THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE ENGINEER FOR APPROVAL PRIOR TO CONSTRUCTION.
- BARS PARTIALLY EMBEDDED IN CONCRETE SHALL BE BENT COLD.
- BAR SPLICES

UNLESS OTHERWISE SPECIFIED, SPLICE LENGTH OF REBARS SHALL BE AS IN THE FOLLOWING TABLES:

32	28	25	20	16	12	BAR DIAMETER (mm)
1760	1540	1375	880	705	530	SPLICE LENGTH Ld (mm)

NOTES:

- c.1) FOR BUNDLED BARS, SPLICED LENGTH Ld SHALL BE MULTIPLIED BY 1.10.
- c.2) FOR THREE (3) BUNDLED BARS, Ld SHALL BE MULTIPLIED BY 1.20.
- c.3) FOR FOUR (4) BUNDLED BARS, Ld SHALL BE MULTIPLIED BY 1.30. c.4) BARS SPLICING NOT INDICATED ON THE DRAWINGS SHALL BE REFERRED TO THE ENGINEER FOR FINAL APPROVAL.
- c.5) WELDED SPLICES, IF APROVED BY THE ENGINEER, SHALL DEVELOP IN TENSION AT LEAST 125% OF THE SPECIFIED YIELD STRENGTH OF THE BARS. IF WELDED, REBARS MUST BE WELDABLE GRADE.
- c.6) NOT MORE THAN 50% OF THE BARS AT ANY ONE SECTION SHALL BE SPLICED.
- c.7) UNLESS OTHERWISE SHOWN ON THE DRAWINGS, THE CLEAR DISTANCE BETWEEN PARALLEL BARS IN A LAYER SHALL NOT BE LESS THAN 1.5 TIMES THE MAXIMUM SIZE OF COARSE AGGREGATE. THE CLEAR DISTANCE BETWEEN LAYERS SHALL NOT BE LESS THAN 25mm NOR ONE BAR DIAMETER. THE BARS IN THE UPPER LAYER SHALL BE PLACED DIRECTLY ABOVE THOSE IN THE BOTTOM LAYER.
- c.8) HOOK AND BENDS.
- a) DIMENSION OF 90-DEGREES AND 180-DEGREES HOOKS

C) CONCRETE COVER TO REINFORCEMENT

THE MINIMUM CONCRETE COVER TO REINFORCEMENT SHALL BE AS FOLLOWS UNLESS OTHERWISE SPECIFIED:

CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND: SLABS, WALLS BEAMS, COLUMNS	CONCRETE EXPOSED TO WEATHER	CONCRETE CAST AGAINST EARTH	STRUCTURES UNDER WATER	TYPE OF STRUCTURE
\$ 20	50	75	75	(mm)

- D) CONSTRUCTION JOINT
- 9 THE POSITION AND FORM OF ANY CONSTRUCTION JOINT SHALL BE AS SHOWN ON DRAWINGS OR AS AGREED WITH THE ENGINEER.
- 9 THE INTERFACE BETWEEN THE FIRST AND SECOND POUR CONCRETE SHALL BE ROUGHENED WITH AN AMPLITUDE OF $6\mathrm{mm}$ MINIMUM.
- E) FALSEWORK, TEMPORARY STRUCTURES
- 9 ALL FALSEWORK AND TEMPORARY STRUCTURES SHALL BE DESIGNED BY THE CONTRACTOR AND DETAIL ARE TO BE SUBMITTED TO THE ENGINEER.

F) FORMWORK


a) UNLESS OTHERWISE SHOWN ON THE DRAWINGS OR APPROVED BY THE ENGINEER, THE FOLLOWING MINIMUM STRIPPING TIMES SHALL BE USED:

STRUCTURAL STEEL

- 9 STRUCTURAL STEEL SHALL CONFORM TO ASTM A36(Fy=248MPa) SPECIFICATIONS. THE CONTRACTOR SHALL PREPARE AND SUBMIT SHOP DRAWINGS FOR ALL STRUCTURAL STEEL WORK. THESE SHOP DRAWINGS SHALL BE APPROVED BY THE ENGINEER BEFORE ANY START OF FABRICATION.
- 5 ALL EXPOSED SURFACES SHALL BE PAINTED FOR CORROSION (GALVANIZE OR EPOXY PAINT) PROTECTION IN ACCORDANCE WITH THE AISC SPECIFICATIONS.
- ALL WEI DINGS SHALL BE IN ACCORDANCE WITH THE AMERICAN WELDING SOCIETY


೦

	MINIMUM TIME	MINIMUM % OF DESIGN STRENGTH
VERTICAL SIDES OF BEAMS, WALL, PILES, PILE CAPS AND COLUMNS, LIFT NOT EXCEEDING 1.2 m.	24 HOURS	70
VERTICAL SIDES OF BEAMS AND WALLS, LIFT EXCEEDING 1.2 $\ensuremath{\text{m}}_{\text{\tiny{1}}}$.	36 HOURS	70
SOFFITS OF MAIN SLABS AND BEAMS	14 DAYS	80
REMOVAL OF PROPS FROM BEAMS AND MAIN SLABS AND OTHER WORK.	14 DAYS	80



PIN DIAMETER: PP P 82 R R R ø10 ø28 콜콜 ø25 ø36

5 DIMENSION FOR STIRRUPS AND TIE HOOKS



N PLAN FOR WWATER EM, S ORIENTAL	
GENERAL NOTES FOR STRUCTURAL WORKS	
PREPARED: JIENSEN TAGLE	FLORANTE T. MARTINEZ
NOLI LEMON M NUEVAS ENGINEER II DATE:	
MARINA A. RABANES CHIEF, PLANNING AND DESIGN SECTION DATE:	
ASSISTA DATE:	•

C.Y. 2025 PROJECT
DETAILED ENGINEERING DESIGN PI
CONSTRUCTION OF RAINWA
COLLECTOR SYSTEM,
LIBERTAD & INITAO, MISAMIS O

MISAMIS ORIENTAL 2ND DISTRICT ENGINEERING OFFICE OF THE DISTRICT ENGINEER Balase St., El Salvador City, Misarris Oriental

REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
REGION - X

PROJECT NAME AND LOCATION:

SHEET CONTENTS:

SUBMITTED:

JIM B. RAMOS
TANT DISTRICT ENGINEER

SET NO.

SHEET NO.

SUMMARY OF QUANTITIES

NO.	DESCRIPTION	QUANTITY	UNIT
PARTI	OTHER GENERAL REQUIREMENTS		
B.5 (1)	PROJECT BILLBOARD/ SIGNBOARD	12.00	e a
B.7 (1)	OCCUPATIONAL SAFETY AND HEALTH PROGRAM	1.00	ī.s.
PART II	CIVIL, MECHANICAL, ELECTRICAL AND SANITARY/ PLUMBING WORKS		
PART A	EARTHWORKS		
803(1)a	STRUCTURE EXCAVATION (COMMON SOIL)	9.22	cu.m.
PART B	PLAIN AND REINFORCED CONCRETE WORKS		
900(1)c	STRUCTURAL CONCRETE (CLASS A, 28 DAYS)	6.44	cu.m.
902(1)a1	REINFORCING STELL (DEFORMED, GRADE 40)	1,463.73	Ģ
PART C	FINISHING		
PART D	PLUMBING/ SANITARY WORKS		
1002(27)	PLUMBING WORKS	1.00	.s



PROJECT NAME AND LOCATION: C.Y. 2025 PROJECT
DETAILED ENGINEERING DESIGN PLAN FOR
CONSTRUCTION OF RAINWATER
COLLECTOR SYSTEM,
LIBERTAD & INITAO, MISAMIS ORIENTAL SHEET CONTENTS:

PREPARED:

DRAFTED:

NOLI LEMON M. NUEVAS ENGINEER II DATE

SUBMITTED:

SET NO.

