

REPUBLIC OF THE PHILIPPINES DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS

CEBU 2ND DISTRICT ENGINEERING OFFICE POBLACION DALAGUETE, CEBU, REGION VII

C.Y. 2025 PROJECT

CONVERGENCE AND SPECIAL SUPPORT PROGRAM: BASIC INFRASTRUCTURE PROGRAM (BIP), FLOOD MITIGATION STRUCTURES PROTECTING PUBLIC INFRASTRUCTURES/FACILITIES, CONSTRUCTION OF DRAINAGE STRUCTURE, BARANGAY LANGTAD, ARGAO, CEBU

ARGAO, CEBU
LINED CANAL 1 = 217.69 M.
LINED CANAL 2 = 63.00 M.

SUBMITTED:

LENARD A. PANUGALINOG
CHIEF, PLANNING AND DESIGN SECTION

DATE:

RECOMMENDED:


ROSALIND R. VASQUEZ
OIC - ASSISTANT DISTRICT ENGINEER

DATE:

SUBMITTED:


SUSAN L. ORNOPIA-AROA
OIC - DISTRICT ENGINEER

ATE:






		INDEX OF SHEETS				
SET	SHEET NO.	SHEET CONTENTS				
	1	COVER SHEET				
Α	2	LOCATION PLAN, PROJECT LENGTH DATA, INDEX OF SHEET, KEY MAP, LOCATION MAP AND VICINITY MAP				
	3	SUMMARY OF QUANTITIES				
	4-5	GENERAL NOTES (SPECIFICATION, DESIGN CRITERIA, SYMBOLS, ABBREVIATIONS & LEGENDS)				
1	6	ITEM SPECIFICATION				
	7-8	GEOTECHNICAL INVESTIGATION REPORT	PRO	JECT LENGTH DA	DATA	
	9	BACK - UP COMPUTATION AND VOLUME REPORT	TYPE	STATION (LIMITS)	LENGTH	
В	10	DPWH STANDARD PROJECT BILLBOARD		SEC 1: STA 0+000.00 TO STA		
	11	TYPICAL ROAD WITH SEAWALL STRUCTURE SECTION	UNED CANAL 1 0+217.69		217.69M	
	12	12 TYPICAL ROAD WITH RCPC SECTION LINED CANAL 2 S	SEC 2: STA 0+000.00 TO STA 0+063.00	63.00M		
	13	TYPICAL FLOOD CONTROL STRUCTURE DETAIL				
	14	SHEET PILE DETAILS	BOX CULVERT	SEC 2: STA 0+000,00	15.05M	
	15	TOPOGRAPHIC SURVEY	TYPE	STATION (LIMITS)	QUANTITY	
c	16	PROJECT ALIGNMENT] '''-	STATION (EIMITS)	QUANTITY	
	17	PLAN AND PROFILE	CATCH BACIN	SEC 2: STA 0+000.00, STA		
	18-26	CROSS - SECTION	CATCH BASIN	0+063.00	2	



KEY MAP



REGION VII MAP

LOCATION MAP



VICINITY MAP



REPUBLIC OF THE PHILIPPINES
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS

CEBU 2ND DISTRICT ENGINEERING OFFICE POBLACION DALAGUETE, CEBU, REGION VII

PROJECT NAME AND LOCATION:

C.Y. 2825 PROJECT

OETALE DE ROMONEERING DESIGN PLAN FOR
CONVENGENCE AND SPECIAL SUPPORT PROGRAMS SUSTAINABLE INTRASTRUCTURE
PROJECTS ALEVATING GAPS (SIEDO), FLORIZON STRUCTURES PROFECTI
MAJOR/STRATEGIC PUBLIC BUILDINGS/FACILITIES, CONSTRUCTION OF SEAWALE
BARANGAY LOCO, COLSO, CEBU

OSLOB, CEBU

OSLOB, CEBU

INDEX OF DRAWINGS
PROJECT INFORMATION SHEET
LOCATION PLAN
KEY MAP, LOCATION MAP, VICINITY MAP

SHEET CONTENTS:

CHARIE Z. BAHENA KEVIN JOSHUA A. TAMANAHA LENARD A. PANUGALINOG
ENGINEER II ENGINEER II CHIEF, PLANNING AND DESIGN SECTION
DATE:
DATE:

SUSAN L. ORNOPIA-AROA

ASSISTANT DISTRICT ENGINEER
DATE:

MA. CHYMBELIN D. IBAL
DISTRICT ENGINEER
DATE:

A 02 03



SUMMARY OF QUANTITIES

ITEM NO.	DESCRIPTION	QTY.	UNIT
B.4(10)	Miscellaneous Survey and Staking	1.00	L.S.
B.5(1)	Project Billboard/Sign Board	3.00	each
B.7(1)	Occupational Safety and Health Program	1.00	L.S.
B.8 (1)	Traffic Management	0.59	month
B.9(1)	Mobilization/Demobilization	1.00	L.S.
101(3)b6	Removal of Actual Structures/Obstruction, 0.30m thick, PCCP (Unreinforced)	1.00	L.S.
900(1)c Clearing and Grubbing		20.59	cu.m.
902(1)a1	902(1)a1 Reinforcing Steel (Deformed), Grade 40		kg
1700 (1) Reinforcing Steel (Deformed), Grade 40		1.00	L.S.
1701 (2) Surplus Common Excavation		1,403.71	cu.m.
1704 (1) a Embankment, From roadway/structure excavation		110.36	cu.m.
1718 (21) b1	Lined Canal, Concrete, Rectangular	280.69	l.m.
1718 (22)	Bedding	139.74	cu.m

REPUBLIC OF THE PHILIPPINES DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
CEBU 2ND DISTRICT ENGINEERING OFFICE POBLACION DALAGUETE, CEBU, REGION VII

PROJECT NAME AND LOCATION:	Γ
C.Y. 2025 PROJECT	1
DETAILED ENGINEERING DESIGN FLAN FOR CONVENGENCE AND SPECIAL SUPPORT PROGRAMS SUSTAINABLE INFRASTRUCTURE PROJECTS ALLEVIATING GAPS (SIRAGA), FLOOD MITIGATION STRUCTURES PROTECTING MAJOR/STRATEGIC PUBLIC BULLDINGS/FACILITIES, CONSTRUCTION OF SEAWALL, BRANKINGAY LODG, SOLOS, CEBU	
OSLOB, CÉBU	L
SEAWALL LENGTH + 151.90 M.	L

S:				
Q	U	Αħ	VT.	


CHARIE Z. BAHENA	KEVIN JOSHUA A. TAM
ENGINEER II	ENGINEER II
ATE:	DATE:


۰		
	LENARD A. PANUGALINOG	SUSAN L. ORNOPIA-ARO
	CHIEF, PLANNING AND DESIGN SECTION DATE ;	ASSISTANT DISTRICT ENGINEED DATE:


AFFROVED	ac i iv
MA. CHYMBELIN D. IBAL	A
DISTRICT ENGINEER DATE:	03











_		
	PROJECT NAME AND LOCATION:	SHEET CON
	DETAILED ENGINEEDING DEGICAL OF AN EGO	TYPICAL CROSS S
	OSLOB, CEBU	
	SEAWALL LENGTH = 151.90 M.	

T CONTENTS:	PREPARED AND DESIGNED:	REVIEWED:	SUBMITTED:	RECOMMENDED:	APPROVED:
CAL ROAD WITH FLOOD CONTROL STRUCTURE SS SECTION					
	CHARIE Z. BAHENA	KEVIN JOSHUA A. TAMANAHA	LENARD A. PANUGALINOG	SUSAN L. ORNOPIA-AROA	MA. CHYMBELIN D. IBAL
	ENGINEER II DATE :	ENGINEER II DATE :	CHIEF, PLANNING AND DESIGN SECTION DATE :	ASSISTANT DISTRICT ENGINEER DATE:	DISTRICT ENGINEER DATE:




MISCELLANEOUS STRUCTURES - REINFORCED CONCRETE LINE CANAL

- 1. REINFORCING STEEL SHALL CONFORM TO AASHTO M31 (ASTM A615), GRADE 40 FOR BARS 16mm AND SMALLER (40 000psi) fy=275.80 MPa.
- 2. SLOPE TOP OF LINED CANAL SHALL BE 2.00% GOING TO THE GUTTER.
- 3. COVERING SHALL BE LOCATED AT EVERY 15m AND/OR AT EVERY CORNER OF THE JUNCTION FOR MAINTENANCE PURPOSES.
- 4. HOOKS AND BENDS

HOOKS AND BENDS SHALL BE AS SHOWN IN THE FOLLOWING TABLE


BAR DIA, dbØ	(40)	ND OKS	LINE CHILD CO.	RUP	STIRRUP TIE
mm	180°	90°	90°	135°	135°
10	125	150	100	100	125
12	150	200	113	113	163
16	175	250	150	138	200




STIRRUP & TIE HOOK STIRRUP TIE

Do = 6 db for db < 30Do = 8.7 db for db > 30

D = 4 db for db < 20 D = 6 db for db > 30





SHEET NO.

11


26

TYPE	DESCRIPTION	UNIT PER METER	QTY
CONCRETE	LINED CANAL W/ COVER	m³/meter	0.31
REIFORCEMENT	LINED CANAL W/ COVER AND METAL GRATING	kg/meter	33.17

REINFORCED CONCRETE LINED CANAL DETAIL B-15 18 SCALE: NTS

224mm LONG - Ø12mm

PLAIN HANDLE BAR



PROJECT NAME AND LOCATION:							
C.Y. 2025 PROJECT							
DETALED ENGINEERING DESIGN FLAN FOR CONVERGENCE AND SPICIAL SUPPORT PROGRAM: SUSTAINABLE INFRASTRUCTURE PROJECTS ALLEWATING GAP'S (SIPAG), ROOM MITIGATION STRUCTURES PROTECTION MAJOR/ STRATEGIC PUBLIC BUILDINGS/ FACILITIES, CONSTRUCTION OF SEAWALL BARANGAY LOOK, OSLOB, CEBU							
OSLOB, CEBU							
SEAWALL LENGTH = 151.90 M.							

SECTION

100

SHEET CONTENTS:	PREPA
REINFORCED CONCRETE LINED CANAL DETAIL	
	DAT

4-10mmØ

CONCRETE CLASS A

12mmØ @ 300

3-10mmØ

REPARED AND DESIGNED:	REVIEWED:	SUBMITTED:	RECOMMENDED:	APPROVED:
CHARIE Z. BAHENA	KEVIN JOSHUA A. TAMANAHA	LENARD A. PANUGALINOG	SUSAN L. ORNOPIA-AROA	MA. CHYMBELIN D. IBA
ENGINEER II DATE :	ENGINEER II DATE :	CHIEF, PLANNING AND DESIGN SECTION DATE:	ASSISTANT DISTRICT ENGINEER DATE:	DISTRICT ENGINEER DATE:



BOX CULVERT (SINGLE AND DOUBLE BARREL), WING WALL

SPECIFICATIONS

DESIGN 1994 AASHTO STANDARD, SPECIFICATIONS FOR HIGH **BRIDGES. 12TH EDITION**

DESIGN LOAD

LIVE LOAD MS-18 (HS20-44)

CONCRETE

ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS OF fc=20.7MPa (3000psi) ALL EXPOSED CORNERS CHAMFER EDGE 20mm. NO CONSTRUCTION JOINT ARE TO BE MADE EXCEPT AS SHOWN WHEN BOTTOM SLAB IS SUBJECTED TO ABRASION, ADD 25mm TO BOTTOM SLAB TO INCREASE COVERAGE ON STEEL.

STEEL REINFORCEMENT

ALL REINFORCING STEEL SHALL BE INTERMEDIATE (GRADE 40) ASTM A-615 WITH DEFORMATIONS CONFORMING TO ASTM A-305.

IN STATING CULVERT SIZE, GIVE WIDTH BY HEIGHT (WIDTH FIRST). WHEN HEIGHT OF FILL, H = 0, THE TOP OF SURFACE OF THE UPPER SLAB SHALL FOLLOW THE CROWN OF THE FINISHED ROADWAY. THE BOX CULVERT SHALL BE CONSTRUCTED ON A LAYER OF LEAN CONCRETE OF 50mm MINIMUM THICKNESS.

LIVE LOAD DISTRIBUTION REINFORCEMENT

WHEN THERE IS LESS THAN 600mm OF FILL ABOVE TOP SLAB OF CULVERT, ADDITIONAL REINFORCEMENT TRANSVERSE TO THE MAIN REINFORCEMENT IS ADDED TO THE BOTTOM OF THE TOP SLAB IN ACCORDANCE WITH AASHTO 1.3.2.E

HEIGHT OF FILL

MAXIMUM HEIGHT OF FILL IS 300mm ABOVE TOP SLAB, FOR HEIGHT OF FILL GREATER THAN 3000mm, SPECIAL DESIGN OF BOX CULVER SHOULD BE DONE.

DIMENSIONS

ALL UNITS ARE IN mm UNLESS OTHERWISE SPECIFIED

FOR ALL THICKNESS LESS THAN 240, STAGGER HORIZONTAL REINFORCEMENT BARS AS SHOWN:

REPUBLIC OF THE PHILIPPINES
RTMENT OF PUBLIC WORKS AND HIGHWAYS

CEBU 2ND DISTRICT ENGINEERING OFFICE

CLEAR	SINGLE BARREL BOX CULVERT													
h		BAR 1		BAR 2		BAR 3		I	BAR 4		BAR 5		BAR 6	
		Ø	SPACING	ø	SPACING	ø	SPACIN	G Ø	5	SPACING	ø	SPACING	Ø	SPACING
1500	180	16	240	16	280	16	240	16	3	240	12	300	12	250
CLEAR		QUANTITY PER METER OF BARREL												
h			SINGLE		DOUBLE				TRIPLE					
	CON	CONCRETE REINFORCEMENT				CONCRETE REINFORCEMENT			CONCRETE		REINFORCEMEN			
1500	1.21		89.6	0	2.34		279.60		3.32		387.10			

ROJECT NAME AND LOCATION


SHEET CONTENTS:

BOX CULVERT (SINGLE) DETAILS

CHARIE Z. BAHENA

KEVIN JOSHUA A. TAMANAHA

ENGINEER II



LENARD A. PANUGALINOG

CHIEF, PLANNING AND DESIGN SECTION

SUSAN L. ORNOPIA-AROA

ASSISTANT DISTRICT ENGINEER

MA. CHYMBELIN D. IBAL

DISTRICT ENGINEER

10 10

26