

LEGEND:

□PB

PULL BOX SIZE AS REQUIRED (FOR VOICE AND DATA OUTLET)

PABX ELECTRONIC PRIVATE AUTOMATIC BRANCH EXCHANGE

□FD FLOOR DISTRIBUTOR SERVER SÉRVER EQUIPMENT

CONCEALED OR EMBEDDED CONDUIT RUN


NOTE:

CONDUIT CAPACITY FOR CABLE


TYPE OF CARLE	NUMBER OF CABLE IN CONDUIT			
TYPE OF CABLE	20mmØC.	25mmØC.	32mmØĊ.	
CAT 5e, 4PAIR, TWISTED CABLE	1-3	4 - 6	7 - 8	

GENERAL NOTES: (TELECOMMUNICATION SYSTEM)

- THE TELECOMMUNICATION INSTALLATIONS SHALL BE DONE IN ACCORDANCE WITH RULES AND PROVISION OF THE LATEST EDITION OF THE PHILIPPINE ELECTRONICS CODE, CONSTRUCTION STANDARDS OF NATIONAL AND LOCAL AUTHORITIES CONCERNED AND WITH THE REQUIREMENTS OF LOCAL TELECOMMUNICATION COMPANY.
- ALL TELECOMMUNICATION WORKS SHALL BE DONE UNDER THE DIRECT AND IMMEDIATE SUPERVISION OF A DULY REGISTERED PROFESSIONAL ELECTRONIC COMMUNICATION ENGINEER.
- THE DESIGN LAYOUT ON THIS PLAN ARE PROVISION FOR CONDUIT WORKS OF VOICE AND DATA OUTLETS. CLOSED CIRCUIT TELEVISION AND PUBLIC ADDRESS SYSTEMS ONLY. FOR THE COMPLETE ELECTRONICS PLAN, THE END-USER SHALL HIRE A REGISTERED PROFESSIONAL ELECTRONICS ENGINEER (PECE) WHO SHALL PREPARE THE COMPLETE AND FINAL ELECTRONICS PLAN /LAYOUT AND OTHER REQUIRED DETAILS /DRAWINGS. SAID PECE SHALL SIGN AND SEAL THE PLAN TO COMPLY WITH R.A. 9292.







PROJECT NAME & LOCÁTION:

GENERAL NOTES
NETWORK CABLING CONDUIT RISER
DIAGRAM

SHEET CONTENTS:



ANDY'S. FRENO

RECOMMENDED

ALVIN A. IGNACIO

69 EC-4

SHEET No.

Calarman, Northern Samar

LEGEND:

□_{PB}

PULL BOX SIZE AS REQUIRED (FOR VOICE AND DATA OUTLET)

PABX

ELECTRONIC PRIVATE AUTOMATIC BRANCH EXCHANGE

□_{FD}

FLOOR DISTRIBUTOR

SÉRVER EQUIPMENT

CONCEALED OR EMBEDDED CONDUIT RUN


NOTE:

CONDUIT CAPACITY FOR CABLE

TYPE OF CABLE	NUMBE	DNDUİT	
THE OF CABLE	20mmØC.	25mmØC.	32mmØG
CAT 5e, 4PAIR, TWISTED CABLE	1-3	4 - 6	7-8

GENERAL NOTES: (TELECOMMUNICATION SYSTEM)

- THE TELECOMMUNICATION INSTALLATIONS SHALL BE DONE IN ACCORDANCE WITH RULES AND PROVISION OF THE LATEST EDITION OF THE PHILIPPINE ELECTRONICS CODE, CONSTRUCTION STANDARDS OF NATIONAL AND LOCAL AUTHORITIES CONCERNED AND WITH THE REQUIREMENTS OF LOCAL TELECOMMUNICATION COMPANY.
- ALL TELECOMMUNICATION WORKS SHALL BE DONE UNDER THE DIRECT AND IMMEDIATE SUPERVISION OF A DULY REGISTERED PROFESSIONAL ELECTRONIC COMMUNICATION ENGINEER.
- THE DESIGN LAYOUT ON THIS PLAN ARE PROVISION FOR CONDUIT WORKS OF VOICE AND DATA OUTLETS, CLOSED CIRCUIT TELEVISION AND PUBLIC ADDRESS SYSTEMS ONLY. FOR THE COMPLETE ELECTRONICS PLAN, THE END-USER SHALL HIRE A REGISTERED PROFESSIONAL ELECTRONICS ENGINEER (PECE) WHO SHALL PREPARE THE COMPLETE AND FINAL ELECTRONICS PLAN /LAYOUT AND OTHER REQUIRED DETAILS /DRAWINGS. SAID PECE SHALL SIGN AND SEAL THE PLAN TO COMPLY WITH R.A. 9292.



NETWORK CABLING CONDUIT RISER DIAGRAM NOT EC-4 SCALE



Republic of the Philippines
PARTMENT OF PUBLIC WORKS AND HIGHWAYS RÉGIONAL OFFICE No. VIII NORTHERN SAMAR FIRST DISTRICT ENGINEERING OFFICE Caterman, Northern Same

PROJECT NAME & LOCÁTION:

SHEET CONTENTS: GENERAL NOTES NETWORK CABLING CONDUIT RISER


NDY S. EREÑO CHIEF, PLANNING & DESIGN SECTI


VIVIAN GIBIACO

ALVIN A. IGNACIO

SHEET No. 69


EC-4





1 GROUND FLOOR CCTV LAYOUT EC-5 SCALE: 1:100M

2 SECOND FLOOR CCTV LAYOUT EC-5 SCALE: 1:100M




PROJECT NAME & LOCATION:

CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING,
UNIVERSITY OF EASTERN PHILIPPINES, CATARMAN, MORTHERN SAI
UNIVERSITY OF EASTERN PRILIPPINES, CATARMAN N. SAMAR

SHEET CONTENTS:

GROUND FLOOR CCTV LAYOUT
SECOND FLOOR CCTV LAYOUT










APPROVED: SET No. SHEET No.

ALVIN A. IGNACIO


DISTRICT ENSINEER

EC-5

70
84



1 ROOF DECK CCTV LAYOUT
EC-6 SCALE: 1:100M



CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, INIVERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SAMAR UNIVERSITY OF EASTERN PHILIPPINES, CATARMAN N. SAMAR

PROJECT NAME & LOCATION:

ROOF DECK CCTV LAYOUT

SHEET CONTENTS:

MAR DIONALD N. EIMAN
ASST. CHIEF, PLANNING & DESIGN SECTION

NDY S. ENEÑO
CHIEF, PLANNING & CHIEF, PLANNING & CHIEF

RECOMMENDED:

VIVIAN GILACO

ASST. DISTRICT ENGINEER

APPROVED:


SET No. SHEE

EC-6


71 84

LEGE	ND & SYMBOLS
IP CLOSED	CIRCUIT TELEVISION (CCTV) SYSTEM
NVR	NETWORK VIDEO RECORDER
a—	BULLET TYPE CCTV CAMERA
MDF	MAIN DISTRIBUTION FRAME
IDF	INTERMEDIATE DISTRIBUTION FRAME










PROJECT NAME & LOCATION: CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, VERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SAMAI UNIVERSITY OF EASTERN PHILIPPINES, CATARMAN N. SAMAR

LEGEND & SYMBOLS CCTV RISER DIAGRAM

SHEET CONTENTS:











SET No. SHEET No. EC-7

72 84

GENERAL NOTES

- 1. CONTRACTOR IS ADVISED TO VISIT AND SURVEY THE PLACE OF INSTALLATION.
- ALL AIR CONDITIONING UNITS AND VENTILATING UNITS TO BE SUPPLIED SHALL BE NEW AND APPROVED PRODUCTS OF REPUTABLE MANUFACTURERS.
- 3. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE CLOSELY HIS WORK WITH THE OTHER TRADES CONCERNED
- 4. REFRIGERANT SUCTION LINES SHALL BE INSULATED WITH 25 mm THICK PREMOULDED ELASTOMERIC RUBBER INSULATION AS MANUFACTURED BY "ARMAFLEX", AEROFLEX OR APPROVED EQUAL.
- 5. INDIVIDUAL WEATHER PROOF TYPE CIRCUIT BREAKER SHALL BE PROVIDED PROVIDED FOR ALL CONDENSING UNITS.
- 6. ALL EXPOSED DRAIN LINES TO THE CEILING SHALL BE PROVIDED WITH INSULATION TYPICAL TO REFRIGERANT PIPING. (REFER TO PIPE INSULATION DETAIL.)
- 7. ALL EXPOSED DRAIN LINES TO THE CEILING SHALL BE PROVIDED WITH INSULATION TYPICAL TO REFRIGERANT PIPING.(REFER TO PIPE INSULATION DETAIL.)
- 8. ALL NECESSARY GOVERNMENT PERMITS SHALL BE SECURED AND FOR ACCOUNT OF THE CONTRACTOR.
- AS-BUILT PLANS SHALL BE PROVIDED BY THIS CONTRACTOR AFTER COMPLETION OF WORKS.
- 10. ALL INSTALLATION WORKS SHALL BE DONE IN A NEAT AND WORK-MANLIKE MANNER
- 11. ALL REFRIGERANT SUCTION LINES EXPOSED INDOORS AND/OR EXPOSED TO WEATHER SHOULD BE PROVIDED WITH GAUGE #24 ALUMINUM CLADDING. (SUBMIT SHOP DRAWING PRIOR TO INSTALLATION)
- 12. ALL ACCU'S AND FCU'S SHALL BE PROVIDED WITH ANGULAR BAR SUPPORTS. (SUBMIT SHOP DRAWING PRIOR TO INSTALLATION)

SCHEDULE OF EQUIPMENT

DESIGNATION	NO. OF UNIT	TYPE	COOLING CAPACITY	POWER INPUT	POWER CONSUMPTION	EER
AIRCONDITION UNIT	11	WALL MOUNTED	1HP	1840W	8.67/HR	13.72KJ/HW (3.81W/W)

LEGENDS:

FAN COIL UNITS

EXHAUST FANS


AIR COOLED CONDENSING UNITS

CEILING FANS

AUTOMATIC SHUTTER LOUVERS

LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & **EXTERIOR FINISHES)**



PROJECT NAME & LOCATION:

SHEET CONTENTS:

GENERAL NOTES SCHEDULE OF EQUIPMENT LEGEND

PREPARED. DESIGNED:

MAR DIONALD N. EIMAN




SET No. SHEET NO

ME-1


73

CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, VERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SAI

ANDY S. EREÑO



GROUND FLOOR AIRCONDITIONING UNIT LAYOUT ME-2 SCALE: 1:100M





LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & **EXTERIOR FINISHES)**



Republic of the Philippines
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS REGIONAL OFFICE No. VIII NORTHERN SAMAR FIRST DISTRICT ENGINEERING OFFICE Cataman, Northern Samar

PROJECT NAME & LOCATION:

SHEET CONTENTS:

DESIGNED:

ANDY S. FREND
CHIEF, PLANNING & DESGN SECTION
Dete:



ALVIN A. IGNACIO

SET No. SHEET No.

ME-2

GROUND FLOOR AC LAYOUT SECOND FLOOR AC LAYOUT CONSTRUCTION (COMPLETION) OF MULT-PURPOSE BUILDING VERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SA

GENERAL NOTES:

- ALL MECHANICAL WORKS SHALL BE INSTALLED IN ACCORDANCE WITH THE LATEST REQUIREMENTS OF THE PHILIPPINE NATIONAL BUILDING CODE AND PHILIPPINE PLUMBING CODE.
- 2. THE TOTAL SCOPE OF WORKS SHALL INCLUDE ALL WORKS DESCRIBED IN PLANS LISTED IN THE TECHNICAL SPECIFICATIONS FOR MECHANICAL WORKS.
- 3. COORDINATE ALL THE DRAWINGS WITH OTHER RELATED DRAWINGS AND SPECIFICATIONS. THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY OF ANY DISCREPANCY FOUND HEREIN. 4. ALL MECHANICAL EQUIPMENT, VALVES AND APPURTENANCES
- SHALL BE ISO CERTIFIED AND APPLICABLE FOR INDUSTRIAL APPLICATIONS UNDER CLASS D ENVIRONMENT.
- THIS CONTRACTOR SHALL SUBMIT THREE (3) COPIES OF ALL TECHNICAL SPECIFICATIONS AS REQUIRED.
- ALL SUBMERSIBLE PUMPS SHALL BE DIRECT DRIVEN BY A CLOSE COUPLED ELECTRIC MOTOR. MAXIMUM OPERATING SPEED SHALL BE 1800 RPM.
- ALL SUBMERSIBLE PUMPS SHALL BE PROVIDED WITH HEAVY DUTY BALL TYPE BEARINGS.
- AIR BLOWERS SHALL BE DESIGNED TO SUIT THE DUTY SPECIFIED IN CAPACITY IN SEWAGE TREATMENT PLANT. MAXIMUM BLOWER OPERATION SPEED SHALL BE 1650 RPM.
- 9. ALL PIPE WORK ASSOCIATED WITH PUMPING UNIT AND ASSOCIATED FITTINGS SHALL BE FLANGED TO PN 16 OR GREATER IN ACCORDANCE WITH ISO 7005-2.
- 10. ALL PIPING WORK SHALL BE PROVIDED WITH PIPE SUPPORTS. 11. PIPE SLEEVES SHALL BE PROVIDED FOR FLOOR AND WALL PARTITION. IT SHALL BE PROVIDED WITH FLANGES AT BOTH ENDS FOR EASE OF MAINTENANCE
- 12. FLANGE GASKET SHALL BE NATURAL RUBBER OR EQUIVALENT. 13. ALL PIPING SHALL BE PROVIDED WITH FLANGES OR UNIONS TO ALLOW FOR THE DISCONNECTION OF THE MAJOR ITEMS OF PLANT WITHOUT DISTURBING THE MAIN PIPING.
- 14. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TESTING AND COMMISSIONING OF THE WHOLE SEWAGE TREATMENT PLANT FACILITIES.
- 15. ALL VALVES SHALL BE DESIGNED FOR A PRESSURE RATING OF 16 BARS AND TEST PRESSURE OF 1.5 TIMES THE PRESSURE RATING.
- 16. ALL BOLT & NUTS FOR FIXING FOR SUBMERGE PORTION AND BLACK IRON WITH EPOXY PAINT FOR EXPOSE AREA.
- 17. ALL PLAN AND PIPE DIMENSION ARE IN MILLIMETER, UNLESS OTHERWISE NOTED.
- 18. CONCRETE MANHOLE SECTIONS SHALL BE IN ACCORDANCE WITH ASTM C-478.
- 19. PRIOR TO BACKFILL THE ENGINEERING STAFF SHALL INSPECT ALL SANITARY SEWER MAINS.
- 20. ALL MAINTENANCE FITTINGS SUCH AS GATE VALVES, BALL

- VALVES, UNIONS, CLEANOUTS, SHALL BE EXPOSED AND ACCESSIBLE.
- 21. NO PIPE SHALL BE EMBEDDED IN STRUCTURAL MEMBERS UNLESS OTHERWISE SPECIFIED OR ALLOWED.
- 22. INSTALLATION OF WATERLINE SYSTEM, PUMPS AND OTHER EQUIPMENTS SHALL ONLY BE DONE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS AND SPECIFICATIONS. 23. ALL STEEL PIPE LINE SHALL BE ACCORDANCE WITH AWS 10.12
- 24. ALL JOINTING MATERIAL/WELDING RODS SHALL BE ACCORDANCE WITH AWS A5.1

25.

MATERIALS:

- 1. ALL MATERIALS SHALL BE NEW UNLESS OTHERWISE SHOWN OR SPECIFIED.
- 2. PROVIDE HANGERS & SUPPORTS APPROVED FOR USE BY PHILIPPINE PLUMBING CODE.
- 3. PIPING MATERIALS AND FITTINGS SHALL BE AS FOLLOWS:
- A.)AIR LINE

SHALL BE BLACK IRON PIPE AND FITTINGS SCHEDULE 40 OR HIGHER.

B.)WATER LINES

SHALL BE POLYVINYL CHLORIDE (uPVC) PIPES SERIES 40 OR HIGHER.

C.)FITTING

SHALL BE SOLVENT CEMENT JOINT TO ASTM D2564

- D.)STORM DRAINAGE LINE / DOWNSPOUT SHALL BE POLYVINYL CHLORIDE (PVC) PIPES SERIES 1000. FITTINGS SHALL BE SOLVENT CEMENT JOINT TO ASTM D2564.
- E.)BUTTERFLY VALVES SHALL BE "EMBRO", OR APPROVED EQUAL.
- F.)CHECK VALVES SHALL BE "KITS", OR APPROVED EQUAL.
- G.)GATE VALVES SHALL BE "KITS", OR APPROVED EQUAL.
- H.)ELECTRO MAGNETIC FLOWMETER
- "SUPMEA" BRAND OR APPROVED EQUAL.

CODES AND STANDARDS:

- A. PHILIPPINE BUILDING CODE
- B. PHILIPPINE PLUMBING CODE
- C. DENR ADMINISTRATIVE ORDER
- D. AMERICAN SOCIETY OF MECHANICAL ENGINEERS
- E. AMERICAN SOCIETY OF TESTING AND MANUFACTURE
- F. AMERICAN NATIONAL STANDARDS INSTITUTE
- G. AMERICAN WELDERS SOCIETY

EQUIPMENT LIST:

ITEM NO.	DESCRIPTION	PHASE	VOLTAGE	HZ
1.0	AERATION BLOWER 1	3φ	230v	60
2.0	AERATION BLOWER 2	3ф	230v	60
3.0	AERATION BLOWER 3	3ф	230v	60
4.0	ANOXIC PUMP 1	Зф	230v	60
5.0	EQT PUMP 1	Зф	230v	60
6.0	EOT PUMP 2	3φ	230v	60
7.0	DECANTER PUMP 1	Зф	230v	60
5.0	DECANTER PUMP 2	3ф	230v	60
9.0	SLUDGE PUMP	3ф	230v	60
10.0	RETURN SLUDGE PUMP	3ф	230v	60
11.0	BOOSTER PUMP 1	3φ	230v	60
12.0	BOOSTER PUMP 2	3φ	230v	60
13.0	CHEMICAL FEED PUMP 1	1ф	230v	60
14.0	CHEMICAL FEED PUMP 2	1ф	230v	60
15.0	CHEMICAL FEED PUMP 3	1ф	230v	60
16.0	CHEMICAL FEED PUMP 4	1ф	230v	60

DAO 2016-08 & 2021-19:

CLASS	BOD	COD	PH	AMMONIA	NITRATE	PHOSPHATE
Α	20mg/L	60mg/L	5-9	0.5mg/L	14mg/L	lmg/L
В	30mg/L	60mg/L	5-9	0 5mg/L	14mg/L	1mg/L
С	50mg/L	100mg/L	6.5-9.5	4mg/L	14mg/L	4mg/L
D	120mg/L	200mg/L	5.5-9.5	7.5mg/L	30mg/L	10mg/L

CLASS	SURF4CTAL/TS	TSS	OIL & GREASE	FECAL COLIFORM	TOTAL
A	2mg/l.	70mg/L	5mg/L	4mg/L	3000mg/L
В	3mg/1,	85mg/L	5mg/L	200mg/L	3000mg/L
С	15mg/L	100mg/L	5mg/L	400mg/L	10,000mg/I
D	30mg/L	150mg/L	15mg/L	800mg/L	15,000mg/

LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & **EXTERIOR FINISHES)**

ALVIN A. IGNACIO



Republic of the Philippines
PARTMENT OF PUBLIC WORKS AND HIGHWAYS REGIONAL OFFICE No. VIII NORTHERN SAMAR FIRST DISTRICT ENGINEERING OFFICE

PROJECT NAME & LOCATION:

SHEET CONTENTS

DESIGNED:

Melka-AR DIONALD N. EIMAN

VIVIAN & BIACO

RECOMMENDE

SET No.


ME-3

84

SHEET No.

SCHEDULE OF EQUIPMENT


NO. OF UNIT	TYPE	VOLTAGE	WATTAGE	MAX HEAD	MAX FLOW	FREQUENCY
1	FLOOR MOUNTED	220V	2760W	128M	2M / H	60 Hz
	NO. OF UNIT	1 FLOOR	NO. OF UNIT TYPE VOLTAGE 1 FLOOR 2201	NO. OF UNIT TYPE VOLTAGE WATTAGE 1 FLOOR 220V 2760W	NO. OF UNIT TYPE VOLTAGE WATTAGE MAX HEAD 1 FLOOR 220V 2750W 100V	1 FLOOR 220W 2750W 400W





LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & EXTERIOR FINISHES)




CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING, INVERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SAMAR
The state of the s

PROJECT NAME & LOCATION:

SHEET CONTENTS:

WATER PUMP LAYOUT
SCHEDULE OF EQUIPMENT









APPROVED:

SET No. SHEET No.

ALVIN A. IGNACIO
DISTRICT ENGINEER

District ENGINEER

76

GENERAL NOTES:


- 1. Types of Fire Extinguishers: The fire code identifies different types of fire extinguishers suitable for various classes of fires, including Class A (ordinary combustibles like wood, paper), Class B (flammable liquids), Class C (flammable gases), Class D (flammable metals), and Class K (cooking oils and fats).
- 2. Adequate Quantity: Fire extinguishers must be provided in sufficient numbers and appropriate types based on the hazard level and occupancy classification of the premises. The fire code specifies the minimum number and capacity of fire extinguishers required.
- 3. Location and Accessibility: Fire extinguishers should be easily accessible, visible, and located in conspicuous positions within the premises. They should be mounted on brackets or stands and placed along exit routes, near staircases, corridors, and fire exits. The fire code provides specific guidelines on the maximum distance to travel to reach a fire extinguisher.
- 4. Proper Maintenance: Fire extinguishers must be maintained in good working condition at all times. Regular inspections, maintenance, and testing should be conducted as per the manufacturer's recommendations and the fire code. This includes checking the pressure gauge, seals, and other components, ensuring they are not damaged or tampered with.
- 5. Training and Awareness: It is essential to provide training to occupants on the proper use of fire extinguishers and their limitations. Building administrators and occupants should be aware of the type and location of extinguishers within the premises.
- 6. Proper Use: Fire extinguishers should be used only when it is safe to do so, and individuals attempting to extinguish fires must be trained on how to use the specific type of extinguisher. It is important to remember the acronym "PASS" - Pull the pin, Aim at the base of the fire, Squeeze the handle, and Sweep from side to side.
- 7. Recharging and Disposal: If a fire extinguisher has been discharged, it must be recharged or replaced promptly to maintain its readiness. Disposal of damaged or expired extinguishers should be done in accordance with local regulations and environmental guidelines.

LEGEND:


FIRE EXTINGUISHER

LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & EXTERIOR FINISHES)



FIRE EXTINGUISHER DETAIL





GENERAL NOTES













FIRE EXTINGUISHER

SCHEDULE OF EQUIPMENT

DESIGNATION	ON QUANTITY WEIGHT TYPE	QUANTITY			T	T			
		GROSS	AGENT	(LOCATION)	DISCHARGE RANGE	DIAMETER	MAXIMUM VOLUME OF PROTECTION	EXTINGUISHING AGENT	REMARKS
FE	4	18.8 lbs.	10 LBS	WALL MOUNTED	6.00 m,	15.2 cm.	51m³	HCFC 123	ENVIRONMENT EDIENDLY BRAND NEW AND DEADLESS.
FE	4	18.8 lbs.	10 LBS	WALL MOUNTED	6.00 m,	15.2 cm.	51m²	HCFC 123	ENVIRONMENT FRIENDLY, BRAND NEW AND








SECOND FLOOR FIRE EXTINGUISHER LAYOUT 2 FP-2 SCALE: 1:100M

LEGEND :

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & EXTERIOR FINISHES)



PROJECT NAME & LOCATION: SHEET CONTENTS: GROUND FLOOR FIRE EXTIGUISHER LAYOUT SECOND FLOOR FIRE EXTIGUISHER LAYOUT SCHEDULE OF EQUIPMENT CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDS VERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN

DESIGNED:

ENGINEER I

REVIEWED:

ANDY S. FREÑO
CHIEF, PLANNING & DESIGN SECTION
Date:

VIVIAN & ASST. DISTRICT ENGINEER Date:

FP-2

SHEET No.

78


84

ALVIN A. IGNACIO

FIRE EXTINGUISHER

SCHEDULE OF EQUIPMENT

SIGNATION	ATION QUANTITY WEIGHT TYPE	QUANTITY									
		GROSS	AGENT	(LOCATION)	DISCHARGE RANGE	DIAMETER	OF PROTECTION	EXTINGUISHING AGENT	REMARKS		
FE	4	18.8 lbs.	10 LBS	WALL MOUNTED	6.00 m.	15.2 cm.	51m²	HCFC 123	ENVIRONMENT FRIENDLY, BRAND NEW AND READY FOR SERVICE		




ROOF DECK

1 FIRE EXTINGUISHER LAYOUT
FP-3 SCALE: 1:100M

LEGEND :

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & EXTERIOR FINISHES)



CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BULLDING,
INVERSITY OF EASTERN PHILIPPINES, CATARDIAN, NORTHERN SAMAR
UNIVERSITY OF EASTERN PHILIPPINES, CATARDIAN IS, SHARE

PROJECT NAME & LOCATION;

SHEET CONTENTS:

ROOF DECK FIRE EXTIGUISHER LAYOUT SCHEDULE OF EQUIPMENT

PREPARED:
BURT BIT ST. LUCINARIO
ACHITECT II
DESIGNED:

ENGINEER II

MAR DIONALD N. EIMAN

ASST. CHEF, PLANNING & DESIGN SECTION
DIRES:

NDY S EREÑO
CHIEF, PLANING SIGN SECTION
Date:


VIVIANE. BIACO
ASST. DISTRICT ENGINEER
Dete:

PROVED: SET No. SHEET No.


ALVIN A. IGNACIO

DISTRICT ENGINEER

FP-3








FIRE ALARM SYSTEM LAYOUT SECOND FLOOR PLAN 2 FP-4 SCALE: 1:100M

LEGEND

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & **EXTERIOR FINISHES**)



CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING INVERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SA

PROJECT NAME & LOCATION:

SHEET CONTENTS: GROUND FLOOR FIRE ALARM SYSTEM SECOND FLOOR FIRE ALARM SYSTEM

BURT BURGET LUCINARIO DESIGNED:

MAR DIONALD N. EIMAN

ANDY S. EREÑO
CHIEF, PLANNING & DESIGN SECTION


RECOMMENDED: VIVIAN BIACO ASST. DISTRICT ENGINEER Date:

SHEET No.

FP-4

80

ALVIN A. IGNACIO




ROOF DECK FIRE ALARM SYTEM FP-5 SCALE:


LEGEND:

NOT INCLUDED IN PHASE II (ARCHITECTURAL SPACES, INTERIOR & **EXTERIOR FINISHES)**

	FDAS LEGEND
SYMBOLS	DESCRIPTION OF ITEM
M	STATION OUTLET / MANUAL CALL POINT
(SD)	SMOKE DETECTOR
B	FIRE ALARM BELL
(HD)	HEAT DETECTOR
EOLR	END OF LINE RESISTOR
FACP	FIRE ALARM CONTROL PANEL




SMOKE/ HEAT DETECTOR SUSPENDED CEILING MOUNTED



FIRE ALARM ASSORTED DETAILS

FIRE PROTECTION NOTES:

- 1. ALL WORKS SHOULD BE DONE IN ACCORDANCE WITH THE LATEST EDITION OF THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CODES NO. 13 & 20, NATIONAL FIRE CODE OF THE PHILIPPINES.
- ALL WORKS SHALL BE EXECUTED IN-CLOSE COORDINATION WITH ALL OTHER TRADES. THE ARCHITECT AND THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY OF ANY CONFLICT.
- THE CONTRACTOR SHALL SUBMIT CATALOGUE / BROCHURES SUBJECT FOR FURTHER TECHNICAL EVALUATION BY THE CONCERNED AUTHORITY (BOD) PRIOR TO PROCUREMENT / INSTALLATION OF THE EQUIPMENT/
- ALL PIPE SIZES ARE IN MILLIMETERS UNLESS OTHERWISE NOTED.
- PIPE SLEEVES SHALL BE PROVIDED FOR ALL PIPES PASSING THRU SLABS, WALLS & BEAMS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TESTING AND COMMISSIONING FOR ALL E UIPMENT INSTALLED.





RECOMMENDED

APPROVED

SHEET No.

FP-5

81

PROJECT NAME & LOCATION: SHEET CONTENTS: FIRE PROTECTION NOTES ROOD DECK FIRE ALARM LAYOUT FDAS LEGEND SD SINGLE RISER DIAGRAM FIRE ALARM ASSORTED DETAILS CONSTRUCTION (COMPLETION) OF MULTI-PURPOSE BUILDING VERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SA Melha DESIGNED: AR DIONALD N. EIMAN

CHIEF, PLANNING & DESCRIPTION SECTION ASST, CHIEF, PLANNING & DESIGN SECTION

VIVIAN BIACO


ALVIN A. IGNACIO DISTRICT ENGINEER


DISTRICT ENGINEERING OFFICE Catarman, Northern Samar

Republic of the Philippines
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS


REGIONAL OFFICE No. VIII


NORTHERN SAMAR FIRST





DPWH STANDARD PROJECT BILLBOARD





(NOT TO SCALE, ALL DIMENSIONS ARE IN MILLIMETERS)

BILLBOARD FRAME

NOT TO SCALE, ALL DIMENSIONS ARE IN MILLIMETERS

Republic of the Philippines
PARTMENT OF PUBLIC WORKS AND HIGHWAYS REGIONAL OFFICE No. VIII NORTHERN SAMAR FIRST DISTRICT ENGINEERING OFFICE Caterman, Northern Samar

PROJECT NAME & LOCATION:

SHEET CONTENTS:

DPWH STANDARD PROJECT BILLBOARD

PREPARED:

ANDY S. ERENO

APPROVED.

SHEET No.

ALVIN A. IGNACIO


83 PB-2


			Government Cen	iter Candahug, Palo,				
Project :					ost :			
	of Project :							
	Project Date	.,		Project	Status		1 - 1	1
-	rruject Date	-						
Duration	Started	Target Date of Completion	Percentage of Completion	As of (Date)	Cost incurred to Date	Date Completed	Remarks	
Duration		Date of	of	As of (Date)	incurred		Remarks	
For particulars or COA Regional Offi	Started compleints about the second	Date of Completion	of Completion	(Date)	incurred to Date	Completed	Remarks	

COA STANDARD PROJECT BILLBOARD

SPECIFICATIONS:

- 1. TARPAULIN, WHITE, 8 FT X 8 FT
- 2. RESOLUTION: 70 DPI
- 3. FONT: HELVETICA
- 4. FONT SIZE: MAIN INFORMATION 3" SUB-INFORMATION - 1"
- 5. FONT COLOR: BLACK
- 6. BACKGROUND COLOR: WHITE





SHEET CONTENTS:

COA PROJECT BILLBOARD

REVIEWED:

RECOMMENDED

APPROVED:

SET No. SHEET No. 84

PB-3 ALVIN A. IGNACIO

PROJECT NAME & LOCATION:



Republic of the Philippines DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS NORTHERN SAMAR 1ST DISTRICT ENGINEERING OFFICE Catarman N. Samar, Region VIII




MATERIALS SOURCE MAP


PROJECT TITLE: CONSTRUCTION (COMPLETION) MULTI-PURPOSE BUILDING, UNIVERSITY OF EASTERN PHILIPPINES, CATARMAN, NORTHERN SAMAR

Nearest Distance from Project site to Materials Source site: 280.6 km

Materials: Sand, Boulders & Gravel

DISTANCE FROM PROJECT SITE TO MATERIALS SOURCE SITE







PREPARED BY:

PROJECT SITE





Republic of the Philippines DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS NORTHERN SAMAR FIRST DISTRICT ENGINEERING OFFICE REGIONAL OFFICE VIII Catarman, Northern Samar

Name of Project: Construction (Completion) of Multi-Purpose Building, University of Fastern Philippines, Cata

ITEM No.	DESCRIPTION	OTY	UNIT	UNIT COST	AMOUNT % Wt.			BAR CHART				
PART A FAC	CILITIES FOR THE ENGINEER				ACIONII	1 90 99		15 CD	30 CD	54.C.D 15 CD	9 CD	
PART B OTH	HER GENERAL REQUIREMENTS											
	mits and Clearances	1.00	Lla	25 454 24			P	0.20				
	ect Billboard/Signboard (DPWH)			35,454.24	35,454.24	+	A					
		1.00		3,669.42	3,669.42	0.03	A	0.03				
	ect Billboard/Signboard (COA)	1.00	each	6,126.25	6,126.25	0.05	P	in the state of th	0.03			
	upational Safety and Health	1.00	l.s.	448,848.08	448,848.08	3.82	P	in the company of the property	P 1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
	ilization/Demobilization	1.00	l.s.	29,534:40	29,534.40	0.25	P	0.13	+		0.13	
	THWORK						1 A				1	
	vidual Removal of Trees, 150-300mm dia. (Small)	1.00	each	1,253.41	1,253.41	0.01	P	0.01				
01(1) Remo	oval of Structures and Obstruction	1.00	l.s.	6,773.46	6,773.46	0.06	P	0.06		~		
03(1)a Struc	cture Excavation (Common Soil)	110.09	cu.m.	332.93	36,652.26		P	0.31				
04(1)a Emba	ankment from Structure Excavation (Common Soil)	88.07	cu.m.	257.76	22,700.93	_	P	0.19				
04(2)a Emba	ankment from Borrow (Common Soil)	616.97	cu.m.	887.76	547,721.28		P					
04(7) Grave	el Fill	12.40		4,283.25	53,112.29		A			9.00		
ART D REIN	NFORCED CONCRETE			1,205.25	33,112.29	0.45	A		The second secon			
00(1)c Struck	tural Concrete, 3000 psi (Class A, 28 days)	15.85	cu.m	11,969.41	189,715.15	1.61	P		1.61			
0(1)i Struct	tural Concrete (Class A, 28 days)	78.03		11,187.33	872,947.35		P		AND DESCRIPTION OF THE PERSON			
2(1)a1 Reinfo	orcing Steel (Deformed Grade 40)	7,139.08	kg	92.32	659,079.86		P					
2(1)a2 Reinfo	orcing Steel (Deformed Grade 60)	6,675.69		93.65	625,178.37	5.32	A		District Control of the Control of t			
3(1) Formy	works and Falseworks	228.38		752.98			A			50(549)		
RTE FINIS	SHINGS AND OTHER CIVIL WORKS		5qiiii	732.50	171,965.58	1.46	A		ACIVE ACIVE			
	entry and Joinery Works	1.00	l.s.	176,056.45	176,056.45	1.50	Р		1.50			
04(1) Rough	h Hardware	1.00		951,270.29	951,270.29		A P		XIJO MARIA			
04(2) Finishi	ing Hardware	1.00		5,140:80		8.09	A					
10(1) Frame	es, Jambs	1.00		3,394.97	5,140.80	0.04	A			0.04		
10(2)a Doors	(Flush)	0.76 s			3,394.97	0.03	A			0.03		
	zed Tiles	113.06 s		4,213.16	3,202.00	0.03	A			0.03		
	nt Plaster Finish			1,640.61	185,487.37	1.58	A			E. S. C. S.		
27(3) Decora		198.56 s		322.77	64,089.21		A			0,56		
		12.46 s		4,094.75	51,020.59	0.43	P	-4			0.43	
	ng Works, Masonry/Concrete	286.33 s		405.57	116,126.86	0.99	P			, 6.99		
	ng Works, Wood	18.89 s	q.m	556.38	10,510.02	0.09	P					
mm	on - Load Bearing (including Reinforcing Steel), 100	99.28 sc	q.m	1,135.14	112,696.69	0.96	P		0.45	The second second		
7(5)d Metal S	Structure Accessories (Steel Plate)	1.26	kg	219.59	276.68		P			0.002		
1(1)a Railing		1.00	S	755,053.50	755,053.50	6.42	P A			U.UU2		

				- COLIGNATE					11,759,719.86		
WORK ACCOMPLISHMENT (PHYSICAL) CASH FLOW (FINANCIAL)				VALUE CUMULATIVE			2,607,337.16 2,607,337.16			9,152,382.7	
			CUMULATIVE				22:17 22:17			77.83 100.00	
WODY ACCOMPLICITMENT (DUVCTCAL)				PERCENT ACCOMPLISHED							
TOTAL 11,759,719.86 100.00											
08(1)	Hand Laid Rock Embankment	43.93	cu.m.	4,051.04	177,962.19	1.51	P		Company of the Compan		
07(1)	Rubble Concrete	39.06	cu.m.	8,051.02	314,472.84	2.67	P				
	DRAINAGE AND SLOPE PROTECTION STRUCTURES										
.106(1)	CCTV System	1.00	l.s.	277,684.85	277,684.85	2.36	P			E1 10 10 10 10 10 10 10 10 10 10 10 10 10	
.105(20)	Network Cabling	1.00	l.s.	406,396.62	406,396.62	3.46	P				CONTRACTOR
104(1)	Auxiliary System	1.00	l.s.	2,920,927.37	2,920,927.37	24.84	P			The contract of the contract o	Consideration of the constant
1103(1)	Lighting Fixtures	1.00	l.s.	101,236.45	101,236.45	0.86	P			ESCHOLISTICS I	
1102(18)	Solar Panel with Inverter, Battery and Other Devices	1.00	l.s.	1,237,824.00	1,237,824.00	10.53	P			10.33	
1102(1)	Panelboard with Main & Branch Breakers	1.00	l.s.	79,379.90	79,379.90	0.68	P			10.GE	
1101(33)	Wires and Wiring Devices	1.00	l.s.	78,156.36	78,156.36	0.66	A				0.46
1100(10)	Conduits, Boxes & Fittings (Conduit Works/Conduit Rough- in)	1.00	l.s.	20,621.52	20,621.52	0.18	A				0.10

Prepared by:

Checked/Submitted by:

Recommending Approval:

Approved:

ABIGAIL KAYE M. FERNANDEZ Admin. Aide I

ALVIN A. IGNACIO District Engineer