

## Republic of the Philippines

## DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS

Bulacan First District Engineering Office

Tikay, City of Malolos, Bulacan Name of Procuring Entity: Bulacan Ist DEO Purchase Request No.24-09-297 Revised on 09/11/2024 Standard Form/Title REQUEST FOR QUOTATION Office/End-User: Maintenance

COMPANY NAME:

ADDRESS:

TEL. NO./FAX NO.: TIN

Please quote your lowest price on the item(s) listed below, subject to the Terms and Conditions stated below and submit your sealed/open quotation duly signed by your representative not later than 10:00 A.M. of September 23, 2024 in the return envelope attached herewith.

## TERMS AND CONDITIONS:

1. All entries must be typewritten or legibly written.

Delivery period within 10 days upon receipt of the approved funded Purchase Order (P.O.) Administrative penalties pursuant to Sec. 69 of the

Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason

3. Warranty shall be for a minimum of three (3) months for supplies & materials,

one year for Equipment from date of acceptance by the end-user.

- 4. Price validity shall be for a period of one hundred twenty (120) calendar days.
- 5. G-EPS Registration Certificate shall be attached upon submission of the quotation.
- 6. Bidders shall submit original brochures showing certifications of the product, if applicable.
- 7. Please indicate the brand for each items being offered.
- 8. The approved budget ceiling for this procurement Is 999,893.00



em lo.	ITEMS & DESCRIPTION	QTY.	UNIT	UNIT PRICE	TOTAL PRIC
	1. Asphalt Plant Mix (Furnished)	12.69	m.t.		
	*				
_	2. Solar Powered Led Roadway Lighting (200watts)	7.00	each		
_	Solar Photovaltaic Panel: 18V/200 Watts (should be greater than 90% after 10				
_	years and less than 80% after 25 years); Lifetime > 25 years; weight < 25 kgs,; Materials-Monocrystalline / Polycrystalline Silicon; Allowable Ambient				
_	Polycrystalline Silicon; Allowable Ambient Temperature Range -40°C to +60°				
_	Battery: Input Voltage 12.8 V; Lithium-Ion Grade A LifePO4 120aH/12.8V				
	Battery; Lifetime- 6 to 8 years; Charging Discharging Cycles- 2000; Charging - 6				
_	to 7 Hours; Working Time under Rainy Days; 8 to 12 days  Charge Controller: Microcomputer Intelelligent Control for Circuit Protection				
$\dashv$	LED Lamp: Industrial Grade High Lumens Chips, Luminous Flux: 21600				
_	Luminous Flux: 6000 to 30,000 Lumens; Lifetime :> 50,000 hours Housing-High				
_	Preasure die cast aluminum with heat management system and rust resistant  Lighting Time: 10/12 hrs./day sustain 8 to 12 days rainy days				
_	IP Rating: IP67 waterproof rating				
_	Warranty Period: 6 years minimum 3.				
_	Mounting Height Pole				
$\neg$	Height: 8.0 meters with 3.0 meters single Mast Arm				
$\dashv$	Round Steel Tapered Post: 4.0 mm Thickness; Botton 200 mm. dia Top 150 mm. dia.	7.00	each		
$\dashv$	Base Plate: 25 mm x 450 mm x 450 mm	7.00	Eacii		
$\dashv$	Stiffener Plate: 4pcs16 mm x 200 mm x 100 mm x 20 mm				
_	Hot Dip Galvanized Anchor Bolt: 4pcs. 25 mm. dia. X 500 mm A307 with nuts and washers				
7	una mastera				
1					

To be used for the supply & delivery of Asphalt Materials and Installation of Solar Street Lights along Manila North Road this district

Warranty:

Brand and Model:

After having carefully read and accepted your general Conditions, I/ We quote you on the item(s) at prices note above.

Please email your quotation at: rfqdpwhbul1deo@gmail.com

Tel. Nos. (044) 794-2245 loc 31448

Telefax: 794-2245

Printed Name/ Signature/ Date

Tel. No./ Cellphone No./ E-mail Address