Republic of the Philippines Department of Public Works and Highways NATIONAL CAPITAL REGION Manila

Name of Procuring Entity		Request for Quotation (P.R.): 2024-05-038			
Revised on		Date: 05/09/2024			
Standard Form/Title	REQUEST FOR QUOTATION	Office/End-User: DPWH-NCR			
COMPANY NAME:					
ADDRESS:					
TEL: NO:/FAX NO::					

Please quote your lowest price on the item(s) listed below, subject to the Terms and Condition listed below and submit your quotation duly signed by your representative not later than 10:00 A.M. of May 22, 2024 in the return sealed envelope attached herewith to the BAC Secretariat, 2nd Floor, 2nd St., Port Area, Manila

TERMS and CONDITION:

Delivery Period

- 1. All entries must be type written or lightly written
- Delivery period within <u>Five (5)</u> calendar days upon receipt of the approved funded Purchase Order (P.O.), Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason.
- Warranty shall be for a minimum of three (3) months for supplies & materials, one (1) year Equipment, from date of acceptance by the end-user
- 4. Price validity shall be for a period of sixty (60) calendar days.
- 5. PHILGEPS Registration Certificate or Registration No./ Mayor's Permit/ DTI or SEC Registration Certificate/ Tax Clearance / Omnibus Sworn Statement (For ABCs above ₱50K) / Income/Business Tax Return (For ABCs above ₱500k) shall be attached upon submission of the quotation.
- 6. Bidders shall submit brochures showing certifications of the product applicable
- 7. Please indicate the brand for each item being offered.
- 8. All documents must be CERTIFIED TRUE COPY.
- 9. The approved budget ceiling for this procurement is Php 755,999.00

Very truly yours,

JOEL F. LIMPENGCO
Assistant Regional Director
BAC Chairperson

Page 1 of 2

ITEM NO.	ITEM & DESCRIPTION	QTY	UNIT	UNIT PRICE	TOTAL AMOUNT	MODEL
	Aluminum sliding door					
	Double pocketype with fix both side using					
	powdercoated with 6mm thick clear tempered					
	glass with transom using 13/4 x 4 tubular					
	and 13/4 x 13/4 tubular, with complete					
	accessories fabrication and installation					
1	Dimension: 97 1/2 x W - 112 3/4	1	set	Р	Р	
2	Dimension: 94 1/2 x W - 79 x 56	1	set	Р	Р	
	-single door pocketype with ransom					
3	Dimension: 18 x W - 35 (Fix)	2	set	P	Р	
4	Recutting and reconfiguration of Partition	1	lot	Р	Р	
	Laminate Partition 150H x 120W x 42mm T					
	with bottom raceway (cut into 120 x 120 L)					
	with installation					
5	Recutting and reconfiguration of Partition	2	lot	Р	P	
	Laminate Partition 150H x 80W x 42mm T					
	with bottom raceway (cut into 120 x 80 L)					
	with installation					
6	Lower corner metal connector (L-leg)	8	рс	Р	P	
7	Lower corner metal connector (L-button)	8	рс	Р	Р	
8	Corner Top Cover (L-shape)	8	рс	Р	Р	

•							
Price Validity	:		Wa	arranty :			
After having c	arefully read and	accepted your Genera	al condition I / We quot	e you on the item	(s) at prices noted	d above.	
				Printed N	lame/Signature		

Republic of the Philippines Department of Public Works and Highways NATIONAL CAPITAL REGION

Manila Page 2 of 2 Name of Procuring Entity Request for Quotation (P.R.): 2024-05-038 Revised on Date: 05/09/2024 Standard Form/Title REQUEST FOR QUOTATION Office/End-User: DPWH-NCR COMPANY NAME: ADDRESS: TEL. NO./FAX NO.: Please quote your lowest price on the item(s) listed below, subject to the Terms and Condition listed below and submit your quotation duly signed by your representative not later than 10:00 A.M. of May 22, 2024 in the return sealed envelope attached herewith to the BAC Secretariat, 2nd Floor, 2nd St., Port Area, Manila TERMS and CONDITION: 1. All entries must be type written or lightly written Very truly yours, 2. Delivery period within __Five (5) __calendar days upon receipt of the approved funded Purchase Order (P.O.), Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason. 3. Warranty shall be for a minimum of three (3) months for supplies & materials, one (1) year JOEL F. LIMPENGCO Equipment, from date of acceptance by the end-user Assistant Regional Director 4. Price validity shall be for a period of sixty (60) calendar days. BAC Chairperson 5. PHILGEPS Registration Certificate or Registration No./ Mayor's Permit/ DTI or SEC Registration Certificate/ Tax Clearance / Omnibus Sworn Statement (For ABCs above ₱50K) / Income/Business Tax Return (For ABCs above ₱500k) shall be attached upon submission of the quotation. 6. Bidders shall submit brochures showing certifications of the product applicable

7. Please indicate the brand for each item being offered. 8. All documents must be CERTIFIED TRUE COPY.

9. The approved budget ceiling for this procurement is Php 755,999.00

ITEM & DESCRIPTION	QTY	UNIT	UNIT PRICE	TOTAL AMOUNT	BRAND AND MODEL
Corner cover (L-cover)	8	рс	Р	P	
Partition table	2	set	P	P	
25mm in PVC edging					
Size: L80x40x25mm					
Panel leg support	2	set	P	P	
	4	unit	P	P	
With Remote Control, removable and washable	panel				
EER Rating: at least 12.1					
Installation	4	lot	P	P	
- High grade copper tubes standard thickness .28.3/8,5/8.					
- Rubber Insulation using 3/4" thickness.					
- Circuit Breaker with all weather box with THHN #10 Supply wire.					
- With ACCU/Condenser support floor bracket using 2"x		2"x3/16"			
with bolts & nut, dyna bolts.					
- Dismantling of existing Air conditioning unit (if applicable)		ole)			
xxx					
GRAND TOTAL =		, in the second second		P	
					•
	Corner cover (L-cover) Partition table 25mm in PVC edging Size: L80x40x25mm Panel leg support 25mm thick, 725 x 38cm Air-Conditioner, 3HP Inverter Wall Split Type Cooling Capacity: 29,520 kJ/h, 1P, 230V, 60Hz, With Remote Control, removable and washable EER Rating: at least 12.1 Installation - High grade copper tubes standard thickness .2 - Rubber Insulation using 3/4" thickness Control Wire using Royal Cord #12 Circuit Breaker with all weather box with THHN - With ACCU/Condenser support floor bracket us with bolts & nut, dyna bolts Dismantling of existing Air conditioning unit (if x x x	Corner cover (L-cover) Partition table 25mm in PVC edging Size: L80x40x25mm Panel leg support 25mm thick, 725 x 38cm Air-Conditioner, 3HP Inverter Wall Split Type 4 Cooling Capacity: 29,520 kJ/h, 1P, 230V, 60Hz, R32 With Remote Control, removable and washable panel EER Rating: at least 12.1 Installation 4 - High grade copper tubes standard thickness .28.3/8,5/ - Rubber Insulation using 3/4" thickness. - Control Wire using Royal Cord #12. - Circuit Breaker with all weather box with THHN #10 Sulation with ACCU/Condenser support floor bracket using 2"x2 with bolts & nut, dyna bolts. - Dismantling of existing Air conditioning unit (if applicable x x x	Corner cover (L-cover) Partition table 2 set 25mm in PVC edging Size: L80x40x25mm Panel leg support 2 set 25mm thick, 725 x 38cm Air-Conditioner, 3HP Inverter Wall Split Type 4 unit Cooling Capacity: 29,520 kJ/h, 1P, 230V, 60Hz, R32 With Remote Control, removable and washable panel EER Rating: at least 12.1 Installation 4 lot - High grade copper tubes standard thickness .28.3/8,5/8. - Rubber Insulation using 3/4" thickness. - Control Wire using Royal Cord #12. - Circuit Breaker with all weather box with THHN #10 Supply wir - With ACCU/Condenser support floor bracket using 2"x2"x3/16" with bolts & nut, dyna bolts. - Dismantling of existing Air conditioning unit (if applicable) x x x	Corner cover (L-cover) Partition table 2 set 2 set P 25mm in PVC edging Size: L80x40x25mm Panel leg support 2 set P 25mm thick, 725 x 38cm Air-Conditioner, 3HP Inverter Wall Split Type Cooling Capacity: 29,520 kJ/h, 1P, 230V, 60Hz, R32 With Remote Control, removable and washable panel EER Rating: at least 12.1 Installation 4 lot High grade copper tubes standard thickness .28.3/8,5/8. Rubber Insulation using 3/4" thickness. Control Wire using Royal Cord #12. Circuit Breaker with all weather box with THHN #10 Supply wire. With ACCU/Condenser support floor bracket using 2"x2"x3/16" with bolts & nut, dyna bolts. Dismantling of existing Air conditioning unit (if applicable) x x x	Corner cover (L-cover) Partition table 2 set P P 2 set P Air-Conditioner, 3HP Inverter Wall Split Type 4 unit P Cooling Capacity: 29,520 kJ/h, 1P, 230V, 60Hz, R32 With Remote Control, removable and washable panel EER Rating: at least 12.1 Installation 4 lot P - High grade copper tubes standard thickness .28.3/8,5/8. - Rubber Insulation using 3/4" thickness. - Control Wire using Royal Cord #12. - Circuit Breaker with all weather box with THHN #10 Supply wire. - With ACCU/Condenser support floor bracket using 2"x2"x3/16" with bolts & nut, dyna bolts. - Dismantling of existing Air conditioning unit (if applicable) x x x

Delivery Period	:	_
Price Validity	:	Warranty :
After having car	refully read and accepted your 0	General condition I / We quote you on the item(s) at prices noted above.
		Printed Name/Signature