



Republic of the Philippines
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS
REGIONAL OFFICE IX
Veterans Avenue Extension, Tetuan, Zamboanga City



Name of Procuring Entity :	DPWH, Regional Office IX, Z.C.	Request for Quotation (P.R. No.) :	25-04-031
Revised on:		Date :	May 15, 2025
Standard Form/Title :	REQUEST FOR QUOTATION		Office/End-User : Management (Proc. Unit)
COMPANY NAME :			
ADDRESS :			
TEL. NO./FAX No :	TIN :		

Please quote your lowest price on the item(s) listed below, subject to the Terms and Conditions stated below and submit your quotation duly signed by your representative not later than 10:00 A.M. of _____ in the return envelope attached herewith, to the Procurement Unit, DPWH Regional Office IX, Veterans Avenue Extension, Tetuan, Zamboanga City.

TERMS and CONDITIONS :

1. All entries must be typewritten or legibly written
2. The delivery period **within 30 calendar days** upon receipt of the approved funded Purchase Order (P.O.). Administrative penalties pursuant to Sec. 69 of the Revised IRR-RA 9184 shall be imposed for non-delivery without valid reason
3. Warranty shall be for a minimum of three (3) months for supplies & materials; one year for Equipment; 3 years IT Equipment from date of acceptance by the end-user.
4. Price validity shall be for a period of sixty (60) calendar days.
5. **PhilG-EPS Registration Certificate, Mayor's Permit, DTI/SEC, Omnibus Sworn Statement (for above 50,000.00), Tax Clearance shall be attached upon submission of the quotation.**
6. Bidders shall submit original brochures of the product .
7. Please indicate the brand for each items being offered.
8. The approved budget ceiling for this procurement is Php 465,000.00

Sgd.

SORAY'YAH M. IBRAHIM, CESO IV

Assistant Regional Director
BAC Chairperson

ITEM NO.	ITEMS & DESCRIPTION	QTY	UNIT	UNIT PRICE	TOTAL PRICE
1	Full Color Laser Multifunction Copier/ <i>Printer/Scanner</i>	1	unit		
	<i>Special Features</i>				
	<i>*Copy/Print Speed: 25 copies/prints per minute</i>				
	<i>*Feeder: 100-Sheets Auto Reverse Document Feeder (ARDF)</i>				
	<i>*Display: Android OS 10.1 Smart Operation Panel</i>				
	<i>*Mobile Printing Capable: Apple AirPrint, Mopria, NFC</i>				
	<i>* Duplex Copying/Printing : Automatic back to back copying and printing</i>				
	<i>*Paper Trays: 2 x 550 sheets Internal Tray/ 1 x 100 sheets Bypass tray</i>				
	<i>*Paper Weight: 52-300 g/m2</i>				
	<i>*Paper Size: Can print up to 12.59 x 49.6 paper size</i>				
	<i>*CPU: ApolloLake E3930 1.3GHz</i>				
	<i>*Memory: 6GB Ram</i>				
	<i>*SSD: 256 GB SSD; 1TB (Option)</i>				
	<i>*Resolution: 4,800 x 1,200 dpi</i>				
	<i>*Network Interface: Ethernet 10 BASE-T/ 100Base-TX/ 1000Base-T, USB Host I/F Type A, USB Device I/F Type B</i>				
	<i>Printer Features</i>				
	<i>*Print Speed: 25 prints per minute</i>				
	<i>*Printer Driver: Standard: PCL5c, PCL6, PostScript 3tm Emulation, PDF direct Emulation</i>				
	<i>*Resolution: 4,800 x 1,200 dpi max.</i>				
	<i>*Network Protocol: TCP/IP (IPv4, IPv6)</i>				

[illegible]

IM C2010/IM C2510/IM C3010

	IM C2010 (ARDF)	IM C2510 (ARDF)	IM C3010 (SPDF)
GENERAL			
Warm-up time	24 seconds	24 seconds	24 seconds
First copy speed: B/W	5.1 seconds	5.1 seconds	4.5 seconds
First copy speed: full colour	7.4 seconds	7.4 seconds	6.9 seconds
Continuous output speed	20 ppm	25 ppm	30 ppm
Memory: standard	6 GB	6 GB	8 GB
Memory: maximum	6 GB	6 GB	8 GB
SSD: standard		256 GB	
SSD: optional		1 TB	
Document Feeder capacity	100 sheets	100 sheets	220 sheets
Weight (kg)	89.7	89.7	99.3
Dimensions WxDxH (mm)	587 x 701 x 913	587 x 701 x 913	587 x 701 x 963
Power source	220 - 240 V, 50 - 60 Hz		
COPIER			
Multiple copying	Up to 999 copies		
Resolution	600 dpi		
Zoom	From 25% to 400% in 1% steps		
PRINTER			
First print speed: B/W	4.5 seconds	4.5 seconds	4 seconds
First print speed: full colour	7 seconds	7 seconds	6.6 seconds
CPU (IM C2010, IM C2510, IM C3010, IM C3510)	ApolloLake E3930 1.3 GHz		
CPU (IM C4510, IM C6010)	ApolloLake E3940 1.6 GHz		
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)		
Printer language: option	Genuine Adobe® PostScript®3™, PDF Direct from Adobe®		
Print resolution: maximum	4,800 x 1,200 dpi equivalent		
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B		
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac), Additional NIC (2 nd port)		
Mobile printing capability	Apple AirPrint, Mopria®, NFC, Ricoh Smart Device Connector		
Windows® environments	Windows® 8.1, Windows® 10, Windows® 11, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019, Windows® Server 2022		
Mac OS environments	Macintosh OS X v10.15 or later		
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX		
SAP® environments	SAP® R/3®, SAP® S/4®		
Other supported environments	IBM iSeries		
SCANNER			
Scanning speed: (A4 LEF, 200dpi, B/W, Full colour)	80 ipm	80 ipm	150 ipm (simplex) 300 ipm (duplex)
Resolution	100 dpi, 200 dpi(default), 300 dpi, 400 dpi, 600 dpi, 1200 dpi*		
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF, Single/multi OCR (optional)		
Scan modes	E-mail, Folder, USB		
*1,200 dpi scanning is supported only with A5 or smaller paper size.			
FAX			
Circuit	PSTN, PBX		
Transmission speed	3 seconds		
Modem speed: maximum	33.6 Kbps		
Resolution: standard	8x3.85 line/mm, 200x100 dpi		
Resolution: option	16x15.4 line/mm, 400x400 dpi		
Compression method	MH, MR, MMR, JBIG		
Scanning speed (A4 LEF)	68 spm	68 spm	90 spm
Memory: standard	4 MB, (320 pages)		
Memory: maximum	60 MB, (4,800 pages)		