



Republic of the Philippines  
DEPARTMENT OF PUBLIC WORKS AND HIGHWAYS  
**NEGROS ORIENTAL 3RD DISTRICT ENGINEERING OFFICE**  
Siaton, Negros Oriental, Region VI

**TECHNICAL SPECIFICATIONS**

Item	Ply	Speed Rating	Load Index	Load Range	Sidewall	Uniform Tire Quality Grade	Max Load (lbs)	Max Inflation Pressure	Measured Rim	Outside Diameter	Rim Width (in)	Section Width	Thread Depth (in 32nds)	Revs per Mile	Tire Weight (lbs)
Tubeless Tire 265/65 R18	8	not less than 118 mph	114-120	Standard Load	Black	not less than 580 AB	not less than 2601 lb	50-70 psi	18 inches	not less than 31.6 inches	7.5-12.0 inches	265-275 inches	not less than 13	not less than 663	35-55 lbs
Tubeless Tire 285/70 R17	10	not less than 100 mph	120-140	Standard Load	Black	not less than 660 AB	not less than 2833 lb	50-70 psi	17 inches	not less than 32.8 inches	7.5-12.0 inches	285-295 inches	not less than 13	not less than 647	50.5-70.5 lb
Tubeless Tire 265/65 R17	8	not less than 118 mph	112-120	Standard Load	Black	not less than 800 AB	not less than 2469 lb	50-70 psi	17 inches	not less than 30.6 inches	7.5-12.0 inches	265-275 inches	not less than 16	not less than 683	42-62 lbs
Tubeless Tire 185 R14 C	8	not less than 68.35 mph	102-115	Standard Load	Black	not less than 460 AB	not less than 1984 lb	44-54 psi	14 inches	not less than 23 inches	5.0-12.0 inches	185-195 inches	not less than 8	not less than 788	10-30 lb
Tire 7.00x15, w/ Flaps and Tube	8	not less than 87 mph	105-115	Standard Load	Black	not less than 780 AB	not less than 2040 lb	60-70 psi	15 inches	not less than 29.5 inches	5.0-12.0 inches	188-199 inches	not less than 11	not less than 741	28-48 lbs
Tubeless Tire 275/65 R18	8	not less than 105 mph	110-150	Standard Load	Black	not less than 660 AB	not less than 2830 lb	50-70 psi	18 inches	not less than 30 inches	7.5-12.0 inches	275-285 inches	not less than 13	not less than 640	50-60 lbs
Tubeless Tire 215x70 R15	8	not less than 130 mph	98-115	Standard Load	Black	not less than 680 AA	not less than 1650 lb	40-55 psi	15 inches	not less than 25.0 inches	5.5-12.0 inches	215-225 inches	not less than 10.5	not less than 770	20-60 lbs
Tubeless Tire 265/60 R18	8	not less than 118 mph	110-120	Standard Load	Black	not less than 580 AB	not less than 2337 lb	50-70 psi	18 inches	not less than 30.5 inches	7.5-12.0 inches	265-275 inches	not less than 11	not less than 685	40-60 lbs
Tire 7.50x15, w/ Flaps and Tube	8	not less than 55.92 mph	135-150	Standard Load	Black	not less than 780 AB	not less than 4806 lb	123.28-140 psi	15 inches	not less than 30.27 inches	5.0-12.0 inches	200-220 inches	not less than 10.5	not less than 715	53.8-73.8 lb
Tubeless Tire 215/70 R15C	8	not less than 130 mph	98-115	Standard Load	Black	not less than 680 AA	not less than 1653 lb	44-54 psi	15 inches	not less than 26.9 inches	5.5-12.0 inches	215-225 inches	not less than 11	not less than 771	20-60 lbs

Manufactured date at least two (2) years upon delivery.

Prepared by:

  
**KYLA MARIE E. QUIMAT**

Engineer II